

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > УДАЛЁННЫЙ ВВОД/ВЫВОД > МНОГОКАНАЛЬНЫЙ



EASION 3M-1LL11

Артикул (SKU): 260105

Удаленный I/O

Коммерческая информация

| | |
|--------------------------|---------------------|
| Код продажи продукта | 260105 |
| Единица Упаковки | 1 шт. |
| Номер таможенного тарифа | 853710980019 |

Техническая информация

General

| | |
|---------------|--------------------------|
| Case Width Mm | (95mmx160mm)x58mm |
| Mounting Type | Rail Mount |

Power Supply

| | |
|-------------|------------------------------------|
| Voltage | 24 - 50 V AC / 12 - 50 V DC |
| Frequency | 45-65 Hz |
| Consumption | <13VA AC / <7W |

Mechanical Properties

| | |
|--------------------|----------|
| Weight G | |
| Packaging Quantity | 1 |

Environmental Conditions

| | |
|----------------------------------|----------------------------------|
| Operating Temperature | -20 to +70 °C |
| Storage Temperature | -20°C..+70°C |
| Relative Humidity Non Condensing | Max.95% (no condensation) |

Digital Output

| | |
|---------------------------|------------------------|
| Number Of Outputs | 12 |
| Switching Current Voltage | 50mA / 5-30V DC |
| Response Time | <18µs |

Relay Output

| | |
|-------------------------------------|--|
| Number Of Outputs | |
| Max Switching Current Voltage Power | |

Input Dry Contact

| | |
|------------------|--|
| Number Of Inputs | |
|------------------|--|

Inputs Wet Contact

| | |
|------------------|--|
| Number Of Inputs | 12 |
| Input Voltage | 12 - 230 V AC/DC |
| Input Current | 1 mA at 5V AC/DC-2,5 mA at 24V AC/DC-4 mA at 230V AC/DC |
| Frequency | 45-65 Hz |
| Isolation Level | 5000Vrms optical insulation |

Communication Rs485 Modbus Rtu

| | |
|-----------|-----------------------|
| Baud Rate | 1200 .. 115200 |
| Stop Bit | 1,2 |
| Slave Id | 1 ..247 |

Communication Micro Usb Modbus Rtu

| | |
|-----------|---|
| Baud Rate | - |
| Stop Bit | - |
| Slave Id | - |

Communication Http Rest

| | |
|-----------|--|
| Interface | |
| Baud Rate | |

Communication Modbus Tcp

Interface

+

Communication Mqtt Http Rest

Interface

Communication Rs232 Modbus Rtu

Baud Rate

1200 .. 115200

Stop Bit

1,2

Slave Id

1 ..247