

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > УДАЛЁННЫЙ ВВОД/ВЫВОД > МНОГОКАНАЛЬНЫЙ



EASION 4M-1LL11

Артикул (SKU): 260205

Удаленный I/O

Коммерческая информация

Код продажи продукта	260205
Единица Упаковки	1 шт.
Номер таможенного тарифа	853710980019

Техническая информация

General

Case Width Mm	(95mmx160mm)x58mm
Mounting Type	Rail Mount

Power Supply

Voltage	24 - 50 V AC / 12 - 50 V DC
Frequency	45-65 Hz
Consumption	<13VA AC / <7W

Mechanical Properties

Weight G	
Packaging Quantity	1

Environmental Conditions

Operating Temperature	-20 to +70 °C
Storage Temperature	-20°C..+70°C

Relative Humidity Non Condensing

Max.95% (no condensation)

Digital Output

Number Of Outputs

12

Switching Current Voltage

50mA / 5-30V DC

Response Time

<18µs

Relay Output

Number Of Outputs

Max Switching Current Voltage Power

Input Dry Contact

Number Of Inputs

Inputs Wet Contact

Number Of Inputs

24

Input Voltage

12 - 230 V AC/DC

Input Current

1 mA at 5V AC/DC-2,5 mA at 24V AC/DC-4 mA at 230V AC/DC

Frequency

45-65 Hz

Isolation Level

5000Vrms optical insulation

Communication Rs485 Modbus Rtu

Baud Rate

Stop Bit

Slave Id

Communication Micro Usb Modbus Rtu

Baud Rate

1200 .. 115200

Stop Bit

1,2

Slave Id

1 ..247

Communication Http Rest

Interface

Baud Rate

Communication Modbus Tcp

Interface	+
-----------	---

Communication Mqtt Http Rest

Interface	
-----------	--

Communication Rs232 Modbus Rtu

Baud Rate	1200 .. 115200
-----------	-----------------------

Stop Bit	1,2
----------	------------

Slave Id	1 ..247
----------	----------------
