

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > УДАЛЁННЫЙ ВВОД/ВЫВОД > МНОГОКАНАЛЬНЫЙ



## EASION 5M-1LL11-D

Артикул (SKU): 260306

Удаленный I/O

### Коммерческая информация

|                          |                     |
|--------------------------|---------------------|
| Код продажи продукта     | <b>260306</b>       |
| Единица Упаковки         | <b>1 шт.</b>        |
| Номер таможенного тарифа | <b>853710980019</b> |

### Техническая информация

#### General

|               |                          |
|---------------|--------------------------|
| Case Width Mm | <b>(95mmx160mm)x58mm</b> |
| Mounting Type | <b>Rail Mount</b>        |

#### Power Supply

|             |                                    |
|-------------|------------------------------------|
| Voltage     | <b>24 - 50 V AC / 12 - 50 V DC</b> |
| Frequency   | <b>45-65 Hz</b>                    |
| Consumption | <b>&lt;13VA AC / &lt;7W</b>        |

#### Mechanical Properties

|                    |          |
|--------------------|----------|
| Weight G           |          |
| Packaging Quantity | <b>1</b> |

#### Environmental Conditions

|                       |                      |
|-----------------------|----------------------|
| Operating Temperature | <b>-20 to +70 °C</b> |
| Storage Temperature   | <b>-20°C..+70°C</b>  |

Relative Humidity Non Condensing

**Max.95% (no condensation)**

### Digital Output

Number Of Outputs

**12**

Switching Current Voltage

**50mA / 5-30V DC**

Response Time

**<18µs**

### Relay Output

Number Of Outputs

Max Switching Current Voltage Power

### Input Dry Contact

Number Of Inputs

**12**

### Inputs Wet Contact

Number Of Inputs

Input Voltage

Input Current

Frequency

Isolation Level

### Communication Rs485 Modbus Rtu

Baud Rate

Stop Bit

Slave Id

### Communication Micro Usb Modbus Rtu

Baud Rate

Stop Bit

Slave Id

### Communication Http Rest

Interface

**Micro USB**

Baud Rate

**38400**

### Communication Modbus Tcp

|           |   |
|-----------|---|
| Interface | + |
|-----------|---|

### Communication Mqtt Http Rest

|           |                                  |
|-----------|----------------------------------|
| Interface | <b>Ethernet 10/100 Base - TX</b> |
|-----------|----------------------------------|

### Communication Rs232 Modbus Rtu

|           |                       |
|-----------|-----------------------|
| Baud Rate | <b>1200 .. 115200</b> |
|-----------|-----------------------|

|          |            |
|----------|------------|
| Stop Bit | <b>1,2</b> |
|----------|------------|

|          |                |
|----------|----------------|
| Slave Id | <b>1 ..247</b> |
|----------|----------------|

---