



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

AVK 35 TIRDS Жёлто-зелёный

Артикул (SKU): 334250

Винтовая заземляющая клемма 35 мм²

Коммерческая информация

Код продажи продукта	334250
Единица Упаковки	25 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.1016 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Grey
Number of Levels	1
Protective Conductor Type	PE
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
Note	DIN raylarinin akim tasima kapasitesine dikkat edilmelidir. / Observe the current carrying capacity of the DIN rails.

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Screw Connection
-----------------	-------------------------

Single-core min. conductor cross-section	6 mm²
--	-------------------------

Single-core max. conductor cross-section	50 mm²
--	--------------------------

Conductor Cross Section Awgkcmil Min	10 AWG
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	2 AWG
--------------------------------------	--------------

Multi-core min. conductor cross-section	6 mm²
---	-------------------------

Multi-core max. conductor cross-section	35 mm²
---	--------------------------

Multi-core min. conductor cross-section with ferrule	6 mm²
--	-------------------------

Multi-core max. conductor cross-section with ferrule	35 mm²
--	--------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	4 mm²
--	-------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	16 mm²
--	--------------------------

Min. Stripping Length	16 mm
-----------------------	--------------

Max. Stripping Length	18 mm
-----------------------	--------------

Internal cylindrical indicator	B9
--------------------------------	-----------

Tightening Torque Min	4 Nm
-----------------------	-------------

Tightening Torque Max	6 Nm
-----------------------	-------------

Rail Tightening Torque Min	1,2 Nm
----------------------------	---------------

Rail Tightening Torque Max	1,5 Nm
----------------------------	---------------

DIMENSIONS

Width	16 mm
-------	--------------

Length	62 mm
--------	--------------

Height Mr 35X75	68,10 mm
-----------------	-----------------

Height MR 35x15	75,60 mm
-----------------	-----------------

Height Mr 32	72,70 mm
--------------	-----------------