



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ПРЕДОХРАНИТЕЛЬНЫЕ КЛЕММЫ

ASK 4LD-220VAC Серый

Артикул (SKU): 351779

Винтовая предохранительная клемма 6 мм² с LED

Коммерческая информация

Код продажи продукта	351779
Единица Упаковки	20 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.029 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-3
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
Fuse	G / 6,35 x 31,75
Fuse Type	Cam / Glass

ELECTRICAL FEATURES

Nominal Current	6,3 A
Nominal Voltage	220 V

CONNECTION DATA

Connection Type	Screw Connection
Single-core min. conductor cross-section	0,34 mm²
Single-core max. conductor cross-section	10 mm²
Conductor Cross Section Awgkcmil Min	22 AWG
Conductor Cross Section Awgkcmil Max	8 AWG
Multi-core min. conductor cross-section	0,34 mm²
Multi-core max. conductor cross-section	10 mm²
Multi-core min. conductor cross-section with ferrule	0,25 mm²
Multi-core max. conductor cross-section with ferrule	6 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,5 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	4 mm²
Min. Stripping Length	9 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	B5
Tightening Torque Min	0,5 Nm
Tightening Torque Max	0,8 Nm

DIMENSIONS

Width	10 mm
Length	75,20 mm
Height Mr 35X75	52,40 mm
Height MR 35x15	59,90 mm