



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ПРЕДОХРАНИТЕЛЬНЫЕ КЛЕММЫ

## ASK 3MLD-110 VAC Серый

Артикул (SKU): 355519

Винтовая предохранительная клемма 4 мм<sup>2</sup> с LED

### Коммерческая информация

|                                  |                     |
|----------------------------------|---------------------|
| Код продажи продукта             | <b>355519</b>       |
| Единица Упаковки                 | <b>30 шт.</b>       |
| Номер таможенного тарифа         | <b>853690950000</b> |
| Вес за единицу, включая упаковку | <b>0.018113 kg.</b> |

### Техническая информация

| PRODUCT FEATURES                      |                        |
|---------------------------------------|------------------------|
| Number of Connections                 | <b>2</b>               |
| Color                                 | <b>Grey</b>            |
| Number of Levels                      | <b>1</b>               |
| Insulation Material                   | <b>PA</b>              |
| UL 94 Flammability Class              | <b>V2</b>              |
| Impulse Voltage Category              | <b>III</b>             |
| Insulation Material Group             | <b>I</b>               |
| Pollution Degree                      | <b>3</b>               |
| Connection According to Standard      | <b>IEC 60947-7-3</b>   |
| Continuous Operating Temperature max. | <b>120 °C</b>          |
| Continuous Operating Temperature min. | <b>-55 °C</b>          |
| Fuse                                  | <b>G / 5x20 - 5x25</b> |
| Fuse Type                             | <b>Cam / Glass</b>     |

## ELECTRICAL FEATURES

|                      |              |
|----------------------|--------------|
| Nominal Current      | <b>10 A</b>  |
| Nominal Voltage      | <b>110 V</b> |
| Maximum Load Current | <b>10 A</b>  |

## CONNECTION DATA

|  |                            |
|--|----------------------------|
| Connection Type  | <b>Screw Connection</b>    |
| Single-core min. conductor cross-section   | <b>0.2 mm<sup>2</sup></b>  |
| Single-core max. conductor cross-section   | <b>6 mm<sup>2</sup></b>    |
| Conductor Cross Section Awgkcmil Min   | <b>24 AWG</b>              |
| Conductor Cross Section Awgkcmil Max   | <b>10 AWG</b>              |
| Multi-core min. conductor cross-section  | <b>0.2 mm<sup>2</sup></b>  |
| Multi-core max. conductor cross-section  | <b>6 mm<sup>2</sup></b>    |
| Multi-core min. conductor cross-section with ferrule                                   | <b>0,25 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section with ferrule                                   | <b>4 mm<sup>2</sup></b>    |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | <b>0,5 mm<sup>2</sup></b>  |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | <b>2.5 mm<sup>2</sup></b>  |
| Min. Stripping Length  | <b>9 mm</b>                |
| Max. Stripping Length  | <b>10 mm</b>               |
| Internal cylindrical indicator   | <b>A4</b>                  |
| Tightening Torque Min  | <b>0.5 Nm</b>              |
| Tightening Torque Max  | <b>0.8 Nm</b>              |

## DIMENSIONS

|                 |                |
|-----------------|----------------|
| Width           | <b>6.2 mm</b>  |
| Length          | <b>54.1 mm</b> |
| Height Mr 35X75 | <b>72.5 mm</b> |
| Height MR 35x15 | <b>80 mm</b>   |