



КЛЕММНЫЕ БЛОКИ > ПРУЖИННЫЕ КЛЕММНЫЕ БЛОКИ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

SRD 4-2Т Жёлто-зелёный

Артикул (SKU): 337200

Клемма типа Cage Clamp 4 мм² 2-слойная клемма заземления

Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 337200 |
| Единица Упаковки | 50 шт. |
| Номер таможенного тарифа | 853690950000 |
| Вес за единицу, включая упаковку | 0.0224 kg. |

Техническая информация

| PRODUCT FEATURES | |
|--|------------------------|
| Number of Connections | 4 |
| Color | Yellow/Green |
| Number of Levels | 2 |
| Protective Conductor Type | PE |
| Insulation Material | PA |
| UL 94 Flammability Class | V0 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-1 |
| Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26 | HL1 - HL2 - HL3 |
| Continuous Operating Temperature max. | 130 °C |
| Continuous Operating Temperature min. | -60 °C |

ELECTRICAL FEATURES

| | |
|-------------------------|-------------|
| Nominal Impulse Voltage | 6 Kv |
|-------------------------|-------------|

CONNECTION DATA

| | |
|-----------------|--------------------------|
| Connection Type | Spring Connection |
|-----------------|--------------------------|

| | |
|--|----------------------------|
| Single-core min. conductor cross-section | 0,08 mm² |
|--|----------------------------|

| | |
|--|-------------------------|
| Single-core max. conductor cross-section | 6 mm² |
|--|-------------------------|

| | |
|--------------------------------------|---------------|
| Conductor Cross Section Awgkcmil Min | 28 AWG |
|--------------------------------------|---------------|

| | |
|--------------------------------------|---------------|
| Conductor Cross Section Awgkcmil Max | 10 AWG |
|--------------------------------------|---------------|

| | |
|---|----------------------------|
| Multi-core min. conductor cross-section | 0,14 mm² |
|---|----------------------------|

| | |
|---|-------------------------|
| Multi-core max. conductor cross-section | 4 mm² |
|---|-------------------------|

| | |
|--|----------------------------|
| Multi-core min. conductor cross-section with ferrule | 0,14 mm² |
|--|----------------------------|

| | |
|--|-------------------------|
| Multi-core max. conductor cross-section with ferrule | 4 mm² |
|--|-------------------------|

| | |
|-----------------------|-------------|
| Min. Stripping Length | 8 mm |
|-----------------------|-------------|

| | |
|-----------------------|--------------|
| Max. Stripping Length | 10 mm |
|-----------------------|--------------|

| | |
|--------------------------------|-----------|
| Internal cylindrical indicator | A4 |
|--------------------------------|-----------|

| | |
|--|-------------------------|
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve | 1 mm² |
|--|-------------------------|

DIMENSIONS

| | |
|-------|---------------|
| Width | 6,2 mm |
|-------|---------------|

| | |
|--------|-----------------|
| Length | 89,70 mm |
|--------|-----------------|

| | |
|-----------------|-----------------|
| Height Mr 35X75 | 51,30 mm |
|-----------------|-----------------|

| | |
|-----------------|-----------------|
| Height MR 35x15 | 58,80 mm |
|-----------------|-----------------|