


КЛЕММНЫЕ БЛОКИ > ПРОЧИЕ ПРОДУКТЫ > ПАНЕЛЬНЫЙ РАЗЪЁМ



КРАР-Т Вил. Серый

Артикул (SKU): 670600

Розетка панели (земля)

Коммерческая информация

Код продажи продукта	670600
Единица Упаковки	4 шт.
Номер таможенного тарифа	853669900018

Техническая информация

PRODUCT FEATURES

Color	Bil.Grey
Insulation Material	PC
UL 94 Flammability Class	V2
Continuous Operating Temperature max.	60 °C
Continuous Operating Temperature min.	-20 °C

ELECTRICAL FEATURES

Nominal Current	16 A
Nominal Voltage	250 V

CONNECTION DATA

Connection Type	Screw Connection
Single-core min. conductor cross-section	0,5 mm²
Single-core max. conductor cross-section	10 mm²

Conductor Cross Section Awgkcmil Min	20 AWG
Conductor Cross Section Awgkcmil Max	4 AWG
Multi-core min. conductor cross-section	0,5 mm²
Multi-core max. conductor cross-section	10 mm²
Multi-core min. conductor cross-section with ferrule	0,5 mm²
Multi-core max. conductor cross-section with ferrule	6 mm²
Min. Stripping Length	10 mm
Tightening Torque Min	0,8 Nm
Tightening Torque Max	1,2 Nm

DIMENSIONS

Width	45 mm
Length	75 mm
Height Mr 35X75	70,5 mm
Height MR 35x15	78 mm