

КЛЕММНЫЕ БЛОКИ &gt; ПРОЧИЕ ПРОДУКТЫ &gt; ПАНЕЛЬНЫЙ РАЗЪЁМ

## КРАР-U Bil. Серый

Артикул (SKU): 670700

Розетка панели UPS

### Коммерческая информация

Код продажи продукта	<b>670700</b>
Единица Упаковки	<b>4 шт.</b>
Номер таможенного тарифа	<b>853669900018</b>

### Техническая информация

#### PRODUCT FEATURES

Color	<b>Bil.Grey</b>
Insulation Material	<b>PC</b>
UL 94 Flammability Class	<b>V2</b>
Continuous Operating Temperature max.	<b>60 °C</b>
Continuous Operating Temperature min.	<b>-20 °C</b>

#### ELECTRICAL FEATURES

Nominal Current	<b>16 A</b>
Nominal Voltage	<b>250 V</b>

#### CONNECTION DATA

Connection Type	<b>Screw Connection</b>
Single-core min. conductor cross-section	<b>0,5 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>10 mm<sup>2</sup></b>
Conductor Cross Section Awgkcmil Min	<b>20 AWG</b>
Conductor Cross Section Awgkcmil Max	<b>4 AWG</b>

Multi-core min. conductor cross-section	<b>0,5 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>10 mm<sup>2</sup></b>
Multi-core min. conductor cross-section with ferrule	<b>0,5 mm<sup>2</sup></b>
Multi-core max. conductor cross-section with ferrule	<b>6 mm<sup>2</sup></b>
Min. Stripping Length	<b>10 mm</b>
Tightening Torque Min	<b>0,8 Nm</b>
Tightening Torque Max	<b>1,2 Nm</b>

## DIMENSIONS

Width	<b>45 mm</b>
Length	<b>75 mm</b>
Height Mr 35X75	<b>70,5 mm</b>
Height MR 35x15	<b>78 mm</b>