


КЛЕММНЫЕ БЛОКИ

DS 1F3x1F3 K1 (СЕРЫЙ)

Артикул (SKU): 328879

Клеммная колодка, 1 мм², двухфазная, 3-полюсная

Коммерческая информация

Код продажи продукта	328879
Единица Упаковки	35 шт.
Номер таможенного тарифа	853690950000

Техническая информация

PRODUCT FEATURES	
Number of Connections	6
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	6 Kv
Nominal Current	13,5 A (at 1 mm²) A
Nominal Voltage	250 V
Maximum Load Current	15 A (with 1,5 mm² conductor cross section) A

CONNECTION DATA

Connection Type	Push-in connection
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	1,5 mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	16 AWG
Multi-core min. conductor cross-section	0,14 mm²
Multi-core max. conductor cross-section	1,5 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	0,75 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A1 / B1

DIMENSIONS

Width	3,60 mm
Length	103,27 mm
Height Mr 35X75	41,95 mm
Height MR 35x15	49,45 mm