


КЛЕММНЫЕ БЛОКИ

DS 10Tx10F K4 (СЕРЫЙ)

Артикул (SKU): 328969

Главная клеммная колодка, 10 мм², 1-фаза + 1-заземление, 2-полюсная



Коммерческая информация

Код продажи продукта	328969
Единица Упаковки	50 шт.
Номер таможенного тарифа	853690950000

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1 / IEC 60947-7-2
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	4 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Push-in connection
-----------------	---------------------------

Single-core min. conductor cross-section	0,2 mm²
------------------------------------------	---------------------------

Single-core max. conductor cross-section	16 mm²
------------------------------------------	--------------------------

Conductor Cross Section Awgkcmil Min	24 AWG
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	6 AWG
--------------------------------------	--------------

Multi-core min. conductor cross-section	0,2 mm²
-----------------------------------------	---------------------------

Multi-core max. conductor cross-section	10 mm²
-----------------------------------------	--------------------------

Multi-core min. conductor cross-section with ferrule	0,25 mm²
------------------------------------------------------	----------------------------

Multi-core max. conductor cross-section with ferrule	10 mm²
------------------------------------------------------	--------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	2,5 mm²
----------------------------------------------------------------------------------------	---------------------------

Min. Stripping Length	16 mm
-----------------------	--------------

Max. Stripping Length	18 mm
-----------------------	--------------

Internal cylindrical indicator	A6
--------------------------------	-----------

DIMENSIONS

Width	10 mm
-------	--------------

Length	119,84 mm
--------	------------------

Height Mr 35X75	49,70 mm
-----------------	-----------------

Height MR 35x15	57,20 mm
-----------------	-----------------