



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

AVK 4RT Желто-зеленый

Артикул (SKU): 334270

Клеммная колодка заземления 4 мм², винтовая

Коммерческая информация

Код продажи продукта	334270
Единица Упаковки	50 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.0148 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Yellow/Green
Number of Levels	1
Protective Conductor Type	PE
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-2
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
Note	DIN raylarının akım tasıma kapasitesine dikkat edilmeli/Observe the current carrying capacity of the DIN rails.

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Screw Connection
-----------------	-------------------------

Single-core min. conductor cross-section	0,2 mm²
------------------------------------------	---------------------------

Single-core max. conductor cross-section	6 mm²
------------------------------------------	-------------------------

Conductor Cross Section Awgkcmil Min	24 AWG
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	10 AWG
--------------------------------------	---------------

Multi-core min. conductor cross-section	0,2 mm²
-----------------------------------------	---------------------------

Multi-core max. conductor cross-section	6 mm²
-----------------------------------------	-------------------------

Multi-core min. conductor cross-section with ferrule	0,25 mm²
------------------------------------------------------	----------------------------

Multi-core max. conductor cross-section with ferrule	4 mm²
------------------------------------------------------	-------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,5 mm²
----------------------------------------------------------------------------------------	---------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	2,5 mm²
----------------------------------------------------------------------------------------	---------------------------

Min. Stripping Length	9 mm
-----------------------	-------------

Max. Stripping Length	10 mm
-----------------------	--------------

Internal cylindrical indicator	A4
--------------------------------	-----------

Tightening Torque Min	0,5 Nm
-----------------------	---------------

Tightening Torque Max	0,8 Nm
-----------------------	---------------

DIMENSIONS

Width	6 mm
-------	-------------

Length	58 mm
--------	--------------

Height Mr 35X75	43,80 mm
-----------------	-----------------

Height MR 35x15	51,30 mm
-----------------	-----------------