



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

## AVK 10TK

Артикул (SKU): 334470

Клеммная колодка заземления 10 мм<sup>2</sup>, винтовая

### Коммерческая информация

Код продажи продукта	<b>334470</b>
Единица Упаковки	<b>25 шт.</b>
Номер таможенного тарифа	<b>853690950000</b>
Вес за единицу, включая упаковку	<b>0.0328 kg.</b>

### Техническая информация

PRODUCT FEATURES	
Number of Connections	<b>2</b>
Color	<b>Yellow/Green</b>
Number of Levels	<b>1</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Impulse Voltage Category	<b>III</b>
Insulation Material Group	<b>I</b>
Pollution Degree	<b>3</b>
Protective Conductor Type	<b>PE</b>
Connection According to Standard	<b>IEC 60947-7-2</b>
Continuous Operating Temperature max.	<b>120 °C</b>
Continuous Operating Temperature min.	<b>-55 °C</b>
Note	<b>Observe the current carrying capacity of the DIN rails.</b>

### ELECTRICAL FEATURES

Nominal Impulse Voltage	<b>8 Kv</b>
-------------------------	-------------

## CONNECTION DATA

Connection Type	<b>Screw Connection</b>
Single-core min. conductor cross-section	<b>0,5 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>16 mm<sup>2</sup></b>
Conductor Cross Section Awgkcmil Min	<b>20 AWG</b>
Conductor Cross Section Awgkcmil Max	<b>6 AWG</b>
Multi-core min. conductor cross-section	<b>0,5 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>16 mm<sup>2</sup></b>
Multi-core min. conductor cross-section with ferrule	<b>0,5 mm<sup>2</sup></b>
Multi-core max. conductor cross-section with ferrule	<b>10 mm<sup>2</sup></b>
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	<b>0,5 mm<sup>2</sup></b>
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	<b>6 mm<sup>2</sup></b>
Min. Stripping Length	<b>10 mm</b>
Max. Stripping Length	<b>12 mm</b>
Internal cylindrical indicator	<b>B6</b>
Tightening Torque Min	<b>1,2 Nm</b>
Tightening Torque Max	<b>1,8 Nm</b>
Rail Tightening Torque Min	<b>0,8 Nm</b>
Rail Tightening Torque Max	<b>1,0 Nm</b>

## DIMENSIONS

Width	<b>10,00 mm</b>
Length	<b>42,10 mm</b>
Height Mr 35X75	<b>44,50 mm</b>
Height MR 35x15	<b>52,00 mm</b>