



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

AVK 50 T Желто-зеленый

Артикул (SKU): 334190

Клеммная колодка заземления 50 мм², винтовая

Коммерческая информация

Код продажи продукта	334190
Единица Упаковки	10 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.166 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Yellow/Green
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Protective Conductor Type	PE
Connection According to Standard	IEC 60947-7-2
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
Note	DIN raylarinin akim tasima kapasitesine dikkat edilmeli. / Observe the current carrying capacity of the DIN rails.

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Screw Connection
-----------------	-------------------------

Single-core min. conductor cross-section	161,5 mm²
--	-----------------------------

Single-core max. conductor cross-section	70 mm²
--	--------------------------

Conductor Cross Section Awgkcmil Min	10 AWG
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	1/0 AWG
--------------------------------------	----------------

Multi-core min. conductor cross-section	25 mm²
---	--------------------------

Multi-core max. conductor cross-section	50 mm²
---	--------------------------

Multi-core min. conductor cross-section with ferrule	25 mm²
--	--------------------------

Multi-core max. conductor cross-section with ferrule	50 mm²
--	--------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	10 mm²
--	--------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	16 mm²
--	--------------------------

Min. Stripping Length	22 mm
-----------------------	--------------

Max. Stripping Length	24 mm
-----------------------	--------------

Internal cylindrical indicator	B10
--------------------------------	------------

Tightening Torque Min	6 Nm
-----------------------	-------------

Tightening Torque Max	310 Nm
-----------------------	---------------

Rail Tightening Torque Min	3 Nm
----------------------------	-------------

Rail Tightening Torque Max	6 Nm
----------------------------	-------------

DIMENSIONS

Width	20 mm
-------	--------------

Length	80 mm
--------	--------------

Height Mr 35X75	77,40 mm
-----------------	-----------------

Height MR 35x15	84,90 mm
-----------------	-----------------

Height Mr 32	82 mm
--------------	--------------