



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

AVK 70-95T Желто-зеленый

Артикул (SKU): 336660

Клеммная колодка винтовая

Коммерческая информация

Код продажи продукта	336660
Единица Упаковки	6 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.25333 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Yellow/Green
Number of Levels	1
Protective Conductor Type	PE
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Protective Conductor Type	PE
Connection According to Standard	IEC 60947-7-2
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C

Note

**DIN raylarının akım tasıma kapasitesine dikkat edilmelidir. /
Observe the current carrying capacity of the DIN rails.**

ELECTRICAL FEATURES

Nominal Impulse Voltage

8 Kv

CONNECTION DATA

Connection Type

Screw Connection

Single-core min. conductor cross-section

25 mm²

Single-core max. conductor cross-section

95 mm²

Conductor Cross Section Awgkcmil Min

4 AWG

Conductor Cross Section Awgkcmil Max

3/0 AWG

Multi-core min. conductor cross-section

35 mm²

Multi-core max. conductor cross-section

95 mm²

Multi-core min. conductor cross-section with ferrule

35 mm²

Multi-core max. conductor cross-section with ferrule

95 mm²

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min

16 mm²

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max

35 mm²

Min. Stripping Length

26 mm

Max. Stripping Length

28 mm

Internal cylindrical indicator

B12

Tightening Torque Min

10 Nm

Tightening Torque Max

15 Nm

Rail Tightening Torque Min

3 Nm

Rail Tightening Torque Max

6 Nm

DIMENSIONS

Width

25 mm

Length

80 mm

Height MR 35x15

98,10 mm

Height Mr 32

95,20 mm