



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > МНОГОУРОВНЕВЫЕ КЛЕММЫ

PIK 2,5RD Серый

Артикул (SKU): 325249

Проходная клеммная колодка 2,5 мм², 2-уровневая, push-in, с перекрестной перемычкой

Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 325249 |
| Единица Упаковки | 100 шт. |
| Номер таможенного тарифа | 853690950000 |
| Вес за единицу, включая упаковку | 0.013 kg. |

Техническая информация

| PRODUCT FEATURES | |
|---------------------------------------|----------------------|
| Number of Connections | 4 |
| Color | Grey |
| Number of Levels | 2 |
| Insulation Material | PA |
| UL 94 Flammability Class | V2 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-1 |
| Continuous Operating Temperature max. | 120 °C |
| Continuous Operating Temperature min. | -55 °C |
| ELECTRICAL FEATURES | |
| Nominal Impulse Voltage | 6 Kv |

| | |
|----------------------|--------------|
| Nominal Current | 24 A |
| Nominal Voltage | 500 V |
| Maximum Load Current | 28 A |

CONNECTION DATA

| | |
|--|----------------------------|
| Connection Type | Screw Connection |
| Single-core min. conductor cross-section | 0,2 mm² |
| Single-core max. conductor cross-section | 4 mm² |
| Conductor Cross Section Awgkcmil Min | 24 AWG |
| Conductor Cross Section Awgkcmil Max | 12 AWG |
| Multi-core min. conductor cross-section | 0,2 mm² |
| Multi-core max. conductor cross-section | 4 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,25 mm² |
| Multi-core max. conductor cross-section with ferrule | 2,5 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | 0,5 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | 1,5 mm² |
| Min. Stripping Length | 9 mm |
| Max. Stripping Length | 10 mm |
| Internal cylindrical indicator | A3 |
| Tightening Torque Min | 0,4 Nm |
| Tightening Torque Max | 0,6 Nm |

DIMENSIONS

| | |
|-----------------|-----------------|
| Width | 5 mm |
| Length | 64 mm |
| Height Mr 35X75 | 61,20 mm |
| Height MR 35x15 | 68,70 mm |