



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ПРЕДОХРАНИТЕЛЬНЫЕ КЛЕММЫ

ASK 3 FLD 48 VDC Серый

Артикул (SKU): 354329

Винтовая предохранительная клемма 4 мм² с LED

Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 354329 |
| Единица Упаковки | 30 шт. |
| Номер таможенного тарифа | 853690950000 |
| Вес за единицу, включая упаковку | 0,0183 kg. |

Техническая информация

| PRODUCT FEATURES | |
|---------------------------------------|------------------------|
| Number of Connections | 2 |
| Color | Grey |
| Number of Levels | 1 |
| Insulation Material | PA |
| UL 94 Flammability Class | V2 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-3 |
| Continuous Operating Temperature max. | 120 °C |
| Continuous Operating Temperature min. | -55 °C |
| Fuse | G / 5X20 - 5X25 |
| Fuse Type | Glass |

ELECTRICAL FEATURES

| | |
|-------------------------|-------------|
| Nominal Impulse Voltage | 6 Kv |
| Nominal Voltage | 48 V |
| Maximum Load Current | 10 A |
| Nominal Current In Fuse | 10 A |

CONNECTION DATA

| | |
|--|----------------------------|
| Connection Type | Screw Connection |
| Single-core min. conductor cross-section | 0,2 mm² |
| Single-core max. conductor cross-section | 6 mm² |
| Conductor Cross Section Awgkcmil Min | 24 AWG |
| Conductor Cross Section Awgkcmil Max | 10 AWG |
| Multi-core min. conductor cross-section | 0,2 mm² |
| Multi-core max. conductor cross-section | 6 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,25 mm² |
| Multi-core max. conductor cross-section with ferrule | 4 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | 0,5 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | 2,5 mm² |
| Min. Stripping Length | 9 mm |
| Max. Stripping Length | 10 mm |
| Internal cylindrical indicator | A4 |
| Tightening Torque Min | 0,5 Nm |
| Tightening Torque Max | 0,8 Nm |

DIMENSIONS

| | |
|-----------------|----------------|
| Width | 6,2 mm |
| Length | 54,1 mm |
| Height Mr 35X75 | 72,5 mm |
| Height MR 35x15 | 80 mm |