

КЛЕММНЫЕ БЛОКИ > ПРОЧИЕ ПРОДУКТЫ > ПАНЕЛЬНЫЙ РАЗЪЁМ



PAР U Серый

Артикул (SKU): 670300

Розетка панели UPS

Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 670300 |
| Единица Упаковки | 6 шт. |
| Номер таможенного тарифа | 853669900018 |
| Вес за единицу, включая упаковку | 0.07 kg. |

Техническая информация

PRODUCT FEATURES

| | |
|---------------------------------------|-----------------|
| Color | Bil.Grey |
| Insulation Material | PC |
| UL 94 Flammability Class | V2 |
| Continuous Operating Temperature max. | 60 °C |
| Continuous Operating Temperature min. | -20 °C |

ELECTRICAL FEATURES

| | |
|-----------------|--------------|
| Nominal Current | 16 A |
| Nominal Voltage | 250 V |

CONNECTION DATA

| | |
|--|---------------------------|
| Connection Type | Screw Connection |
| Single-core min. conductor cross-section | 0,5 mm² |
| Single-core max. conductor cross-section | 10 mm² |

| | |
|--|---------------------------|
| Conductor Cross Section Awgkcmil Min | 20 AWG |
| Conductor Cross Section Awgkcmil Max | 4 AWG |
| Multi-core min. conductor cross-section | 0,5 mm² |
| Multi-core max. conductor cross-section | 10 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,5 mm² |
| Multi-core max. conductor cross-section with ferrule | 6 mm² |
| Min. Stripping Length | 10 mm |
| Tightening Torque Min | 0,8 Nm |
| Tightening Torque Max | 1,2 Nm |

DIMENSIONS

| | |
|-----------------|-----------------|
| Width | 42 mm |
| Length | 74,80 mm |
| Height Mr 35X75 | 49 mm |
| Height MR 35x15 | 56,50 mm |