



КЛЕММНЫЕ БЛОКИ > КЛЕММНЫЕ КОЛОДКИ С ВСТАВНЫМ КРЕПЛЕНИЕМ > КЛЕММЫ ДЛЯ ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

## РҮК 4CD\_В Серый

Артикул (SKU): 307689

Компонентная клеммная колодка 4 мм<sup>2</sup>, 2 входа – 2 выхода, push-in (диод)

### Коммерческая информация

|                                  |                     |
|----------------------------------|---------------------|
| Код продажи продукта             | <b>307689</b>       |
| Единица Упаковки                 | <b>45 шт.</b>       |
| Номер таможенного тарифа         | <b>853690950000</b> |
| Вес за единицу, включая упаковку | <b>0.012 kg.</b>    |

### Техническая информация

| PRODUCT FEATURES                      |                      |
|---------------------------------------|----------------------|
| Number of Connections                 | <b>4</b>             |
| Number of Levels                      | <b>1</b>             |
| Protective Conductor Type             | <b>PE</b>            |
| Insulation Material                   | <b>PA</b>            |
| UL 94 Flammability Class              | <b>V2</b>            |
| Impulse Voltage Category              | <b>III</b>           |
| Insulation Material Group             | <b>I</b>             |
| Pollution Degree                      | <b>3</b>             |
| Connection According to Standard      | <b>IEC 60947-7-1</b> |
| Continuous Operating Temperature max. | <b>120 °C</b>        |
| Continuous Operating Temperature min. | <b>-55 °C</b>        |
| ELECTRICAL FEATURES                   |                      |
| Nominal Impulse Voltage               | <b>8 Kv</b>          |

|                      |               |
|----------------------|---------------|
| Nominal Current      | <b>32 A</b>   |
| Nominal Voltage      | <b>1000 V</b> |
| Maximum Load Current | <b>41 A</b>   |

## CONNECTION DATA

|  |                            |
|--|----------------------------|
| Connection Type  | <b>Push-In Connection</b>  |
| Single-core min. conductor cross-section   | <b>0,34 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section   | <b>6 mm<sup>2</sup></b>    |
| Conductor Cross Section Awgkcmil Min   | <b>22 AWG</b>              |
| Conductor Cross Section Awgkcmil Max   | <b>10 AWG</b>              |
| Multi-core min. conductor cross-section  | <b>0,25 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section  | <b>4 mm<sup>2</sup></b>    |
| Multi-core min. conductor cross-section with ferrule                                   | <b>0,34 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section with ferrule                                   | <b>4 mm<sup>2</sup></b>    |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | <b>1 mm<sup>2</sup></b>    |
| Min. Stripping Length  | <b>9 mm</b>                |
| Max. Stripping Length  | <b>10 mm</b>               |
| Internal cylindrical indicator   | <b>A4</b>                  |

## DIMENSIONS

|                 |                 |
|-----------------|-----------------|
| Width           | <b>6 mm</b>     |
| Length          | <b>85,70 mm</b> |
| Height Mr 35X75 | <b>44 mm</b>    |
| Height MR 35x15 | <b>51,5 mm</b>  |