



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ТРАНСФОРМАТОРНЫЕ КЛЕММНЫЕ БЛОКИ

TRV 4 Оранжевый

Артикул (SKU): 422017

Трансформаторные клеммные колодки винтового типа, 4 мм²

Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 422017 |
| Единица Упаковки | 50 шт. |
| Номер таможенного тарифа | 853690950000 |
| Вес за единицу, включая упаковку | 0.0068 kg. |

Техническая информация

| PRODUCT FEATURES | |
|---------------------------------------|-----------------------------|
| Number of Connections | 3 |
| Color | Orange |
| Number of Levels | 1 |
| Insulation Material | PA |
| UL 94 Flammability Class | V2 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC60998-1 / 61558-1 |
| Continuous Operating Temperature max. | 120 °C |
| Continuous Operating Temperature min. | -55 °C |

| ELECTRICAL FEATURES | |
|-------------------------|-------------|
| Nominal Impulse Voltage | 8 Kv |

| | |
|----------------------|-------------------------------------|
| Nominal Current | 25 A (at 4 mm²) A |
| Nominal Voltage | 500 V |
| Maximum Load Current | 32 A |

CONNECTION DATA

| | |
|--|----------------------------|
| Connection Type | Screw Connection |
| Single-core min. conductor cross-section | 0,2 mm² |
| Single-core max. conductor cross-section | 6 mm² |
| Conductor Cross Section Awgkcmil Min | 24 AWG |
| Conductor Cross Section Awgkcmil Max | 10 AWG |
| Multi-core min. conductor cross-section | 0,2 mm² |
| Multi-core max. conductor cross-section | 6 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,25 mm² |
| Multi-core max. conductor cross-section with ferrule | 4 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | 0,5 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | 2,5 mm² |
| Min. Stripping Length | 9 mm |
| Max. Stripping Length | 10 mm |
| Internal cylindrical indicator | B4 |
| Tightening Torque Min | 0,5 Nm |
| Tightening Torque Max | 0,8 Nm |

DIMENSIONS

| | |
|--------|-----------------|
| Width | 7,50 mm |
| Length | 28,20 mm |
| Height | 35 mm |