

КЛЕММНЫЕ БЛОКИ > ПРОЧИЕ ПРОДУКТЫ > ПАНЕЛЬНЫЙ РАЗЪЁМ



PAP LU Серый

Артикул (SKU): 670400

UPS LED Панельная розетка

Коммерческая информация

Код продажи продукта	670400
Единица Упаковки	6 шт.
Номер таможенного тарифа	853669900018
Вес за единицу, включая упаковку	0.07 kg.

Техническая информация

PRODUCT FEATURES

Color	Bil.Grey
Insulation Material	PC
UL 94 Flammability Class	V2
Continuous Operating Temperature max.	60 °C
Continuous Operating Temperature min.	-20 °C

ELECTRICAL FEATURES

Nominal Current	16 A
Nominal Voltage	250 V

CONNECTION DATA

Connection Type	Screw Connection
Single-core min. conductor cross-section	0,5 mm²
Single-core max. conductor cross-section	10 mm²

Conductor Cross Section Awgkcmil Min	20 AWG
Conductor Cross Section Awgkcmil Max	4 AWG
Multi-core min. conductor cross-section	0,5 mm²
Multi-core max. conductor cross-section	10 mm²
Multi-core min. conductor cross-section with ferrule	0,5 mm²
Multi-core max. conductor cross-section with ferrule	6 mm²
Tightening Torque Min	0,8 Nm
Tightening Torque Max	1,2 Nm

DIMENSIONS

Width	42 mm
Length	74,80 mm
Height Mr 35X75	49 mm
Height MR 35x15	56,50 mm