

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ >
СИГНАЛЬНЫЕ ПАНЕЛИ (АННУНЦИАТОРЫ)



ALRC-6(24VAC/DC)

Артикул (SKU): 604610

Реле управления сигнализацией

Коммерческая информация

Код продажи продукта	604610
Единица Упаковки	1 шт.
Номер таможенного тарифа	853180709000

Техническая информация

General	
Connection Type	Screw terminal
Time Interval	----
Integrated Buttons	3 (Horn, Delete, Test)
Siren	---
Real Time Data Recording	---
Battery Life	---
Protection Class	IP50 (front)IP20 (back)
Weight G	274
Packaging Quantity	1
Diagrams	---
DIMENSIONS	---
Power Supply	
Frequency	45-65Hz
Consumption	AC/DC 24V ± %30

Environmental Conditions

Operating Temperature	-20°C +60°C
Storage Temperature	-40°C +75°C
Relative Humidity Non Condensing	Max. 95%

Communication

Protocol	----
Baud Rate	----
Parity	
Stop Bit	
Slave Id	
Isolation	----

Input Signal

Voltage	AC / DC 24V
Frequency	45-65Hz
Quantity	6
Response Time	25±10ms

Output Connections

Output Type	Relay
Number of Connections	8
Type	1 NO (SPST)
Max Values Ac	5A/277V;1385VA
Max Values Dc	5A/30VDC;150W
Mechanical Operating Life	=10⁸ operation
Electrical Operating Life No Side	1x10⁵(5A@250VAC)

Window

Quantity	6
Color	Red
Size Mm	30.5 x 21.6
Illumination	With 4 pcs. red leds

Fast Flashing	90 Flash / Min.
Slow Flashing	---
Marking	Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.

DIMENSIONS

Frontoverall Dimensions Height Mm	96
Frontoverall Dimensions Width Mm	96
Panel Cutout Dimensions Height Mm	89.6
Panel Cutout Dimensions Width Mm	89.6
Panel Cutout Dimensions Depth Mm	66