

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > КОММУНИКАЦИОННЫЕ ИНТЕРФЕЙСЫ > ШЛЮЗ



2G GPRS Шлюз

Артикул (SKU): 601440

2G GPRS шлюз

Коммерческая информация

Код продажи продукта	601440
Единица Упаковки	1 шт.

Техническая информация

CONNECTION DATA

Connection Type	Screw terminal
-----------------	-----------------------

General

Case Width Mm	17,5
Configuration	Configuration through USB Micro USB connection interface
Led Indicators	+
Reset Function	+
Esd Protection	+
Supported Drivers	Microsoft .NET Framework 3.5 üzeri windows isletim sistemleri
Supported Protocols	MODBUS TCP; MODBUS RTU over TCP; MODBUS ACII over TCP
Isolation	1.5kV RMS

Power Supply

Voltage	11-30VDC
Frequency	45-65Hz
Consumption	1.2W DC

Mechanical Properties

Weight G	
Protection Class	IP20
Mounting Type	
Packaging Quantity	1

Environmental Conditions

Operating Temperature	
Storage Temperature	
Relative Humidity Non Condensing	%95 non-condensing

Serial Interface

Number Of Ports	1
Serial Connection Standard	RS485
Server Mode	64
Receiver Mode	(-)
Baud Rate	300 to 115200 bps
Data Bits	8
Stop Bits	1 or 2
Parity	---, Double, Single

Gprs Interface

Simusim	3V/1.8V
Quad Band	850/900/1800/1900MHz
Downlink	Class 12 85.6kbps
Uplink	Class 12 85.6kbps
Gprs Mobile Station	Class B
Compliant To Gsm Phase 22	Phase 2/2+ Class 4 (2W @850/900MHz) Class 1 (1W @1800/1900MHz)