

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРЕОБРАЗОВАТЕЛИ > ПРЕОБРАЗОВАТЕЛИ  
НАПРЯЖЕНИЯ



## VT3-AC-24

Артикул (SKU): 600103

Преобразователь истинного RMS напряжения

### Коммерческая информация

Код продажи продукта	<b>600103</b>
Единица Упаковки	<b>1 шт.</b>
Номер таможенного тарифа	<b>854370900019</b>
Вес за единицу, включая упаковку	<b>0.076 kg.</b>

### Техническая информация

General	
Connection Type	<b>Screw terminal</b>
Protection Class	<b>IP20</b>
Weight G	<b>76</b>
Packaging Quantity	<b>1</b>
Case Width Mm	<b>36</b>
Mounting Type	<b>Panel or Rail</b>
Isolation	<b>1.5 kVrms, 3-way</b>
Response Time	<b>350ms</b>
Linearity	<b>&lt;0.2%</b>
Ripple	<b>&lt;80mV</b>
Accuracy	<b>&lt;0.2% (full scale, 25°C)</b>
Temperature Coefficient	<b>150 ppm/°C</b>
Test Voltage Between Input Output	<b>4 kV during 1 min.</b>

## Current Measurement Input

Power Consumption	<b>&lt;1.5W DC / &lt;4VA AC</b>
-------------------	---------------------------------

## Power Supply

Voltage	<b>10-36V DC</b>
---------	------------------

Frequency	<b>--</b>
-----------	-----------

## Environmental Conditions

Operating Temperature	<b>-20°C +60°C</b>
-----------------------	--------------------

Storage Temperature	<b>-40°C +75°C</b>
---------------------	--------------------

Relative Humidity Non Condensing	<b>Max. 95%</b>
----------------------------------	-----------------

## Emc Emi

Radiated Emission Test 61000 6 2Ac	<b>2012, 61000-6-4</b>
------------------------------------	------------------------

## Input Signal

Frequency	<b>40-70 Hz</b>
-----------	-----------------

Instantaneous Overload	<b>&lt;2xU Input Max. Range (5 pulses 1 sec.)</b>
------------------------	---

Continuous Overload	<b>Max. 600V</b>
---------------------	------------------

Input Impedance	<b>240 Ohm</b>
-----------------	----------------

## Input Signal Adjustable Voltage Range

0 24Vac	<b>+</b>
---------	----------

0 36Vac	<b>+</b>
---------	----------

0 54Vac	<b>+</b>
---------	----------

0 80Vac	<b>+</b>
---------	----------

0 120Vac	<b>+</b>
----------	----------

0 170Vac	<b>+</b>
----------	----------

0 250Vac	<b>+</b>
----------	----------

0 400Vac	<b>+</b>
----------	----------

0 450Vac	<b>+</b>
----------	----------

0 500Vac	<b>+</b>
----------	----------

0 24Vdc	<b>--</b>
---------	-----------

0 54Vdc	--
0 120Vdc	--
0 250Vdc	--
0 450Vdc	--

### Input Signal Adjustable Current Range

0 1Aac	---
0 2Aac	--
0 3Aac	--
0 4Aac	--
0 5Aac	--

### Output Type

0 20Ma	+
4 20Ma	+
20Ma	+
20 0Ma	+
20 4Ma	+
0 5V	+
10V	+
10 0V	+

### Analog Output

Max Current	<b>24 mA</b>
Max Voltage	<b>12V</b>
Max Load	<b>10 0 (for voltage) / 600 Ohm (for current)</b>