



ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРЕОБРАЗОВАТЕЛИ > ПРЕОБРАЗОВАТЕЛИ СИГНАЛОВ

## Ascon 341

Артикул (SKU): 602330

Термопарный преобразователь

### Коммерческая информация

|                                  |                     |
|----------------------------------|---------------------|
| Код продажи продукта             | <b>602330</b>       |
| Единица Упаковки                 | <b>1 шт.</b>        |
| Номер таможенного тарифа         | <b>854370900019</b> |
| Вес за единицу, включая упаковку | <b>0.042 kg.</b>    |

### Техническая информация

| General                      |   |
|------------------------------|---|
| Connection Type              | <b>Screw terminal</b>                     |
| Protection Class             | <b>IP20</b>                               |
| Weight G                     | <b>42</b>                                 |
| Packaging Quantity           | <b>1</b>                                  |
| DIMENSIONS                   | --  |
| Case Width Mm                | <b>17,5</b>                               |
| Mounting Type                | <b>Rail Mounted</b>                       |
| Isolation                    | <b>3 way - 1,5 kV RMS</b>                 |
| Measurement Error Full Scale | <b>&lt; 0.2% (Full Scale)</b>             |
| Response Time                | <b>0 - 20 Hz</b>                          |
| Temperature Coefficient      | <b>= 0.004%/°C</b>                        |
| Sensor Fault Indication      | <b>M1 M2 leds indication combinations</b> |

### Power Supply

|         |                  |
|---------|------------------|
| Voltage | <b>18-30V DC</b> |
|---------|------------------|

## Environmental Conditions

|                                  |                     |
|----------------------------------|---------------------|
| Operating Temperature            | <b>-20 / +60 °C</b> |
| Storage Temperature              | <b>-40°C +75°C</b>  |
| Relative Humidity Non Condensing | <b>Max. 95%</b>     |

## Emc Emi

|                                    |                        |
|------------------------------------|------------------------|
| Radiated Emission Test 61000 6 2Ac | <b>2012, 61000-6-4</b> |
|------------------------------------|------------------------|

## Output

|                     |   |
|---------------------|---|
| Output Signal       | <b>0 .. 5V, 0 .. 10V, -10 .. 10V, 0 .. 20mA, 4 .. 20mA, -20 .. 20mA</b> |
| Linear Output Range | <b>---</b>  |
| Max Load            | <b>= 600 Ohm ( Current Input ), = 10K Ohm ( Voltage Output )</b>        |
| Ripple              | <b>---</b>  |

## Input

|              |   |
|--------------|---|
| Input Type   | <b>PNP, NPN, Namur, Push-Pull, Dry contact</b>  |
| Input Signal | <b>0 .. 100 kHz configurable via knobs 0...150 kHz can be learned from input signal</b> |