



СОЕДИНИТЕЛИ > MIL-DTL-38999 (СТАНДАРТ) > СЕРИЯ III

## D38999/20WJ90PN

Артикул (SKU): 936WJ90PN

Кабельный соединитель

### Коммерческая информация

|                      |                  |
|----------------------|------------------|
| Код продажи продукта | <b>936WJ90PN</b> |
| Единица Упаковки     | <b>1 шт.</b>     |

### Техническая информация

| PRODUCT FEATURES                      |  |
|---------------------------------------|--|
| Continuous Operating Temperature max. | <b>175 °C</b>                          |
| Continuous Operating Temperature min. | <b>65 °C</b>                           |
| Features                              | <b>MIL-DTL-38999</b>                   |
| Connector Type                        | <b>Plug</b>                            |
| Housing Size                          | <b>25(J)</b>                           |
| Number Of Contacts                    | <b>46 Ad.</b>                          |
| Placement                             | <b>j-90</b>                            |
| Housing Material                      | <b>Aluminium</b>                       |
| Housing Color                         | <b>Khaki Green</b>                     |
| Housing Coating                       | <b>Cadmium</b>                         |
| Contact Type                          | <b>Pin (40#20) (4#16) (2#8 Twinax)</b> |
| Wire Gauge                            | <b>24,22,20,18,16 AWG</b>              |
| Contact Material                      | <b>Au/Cu</b>                           |
| Ingress Protection                    | <b>IP67</b>                            |
| Sealing Material                      | <b>Silicon</b>                         |
| Emi Shielding                         | <b>+</b>                               |

|                |            |
|----------------|------------|
| Mating Cycles  | <b>500</b> |
| Polarization   | <b>N</b>   |
| Service Rating | <b>I</b>   |

## **ELECTRICAL FEATURES**

|                                |                    |
|--------------------------------|--------------------|
| Nominal Current                | <b>7,5-13 A</b>    |
| Operating Voltage Ac V Rms Max | <b>1800V AC/DC</b> |

---