



СОЕДИНИТЕЛИ > MIL-DTL-38999 (СТАНДАРТ) > СЕРИЯ III

## D38999/24WJ90SC

Артикул (SKU): 934WJ90SC

Grade	A	B (max)	C (max)	D (max)	E (max)	F	G Dia	d	P
09	16.50	9.90	3.20	30.50	24.00	27.00	M12*1.6g	17.70	16.99
11	19.30	9.90	3.20	35.30	27.00	31.80	M15*1.6g	20.85	19.52
13	24.00	9.90	3.20	38.60	32.00	34.90	M15*1.6g	25.58	24.25
15	27.20	9.90	3.20	41.80	36.00	38.10	M20*1.6g	28.80	27.53
17	28.40	9.90	3.20	44.80	37.00	41.30	M20*1.6g	31.98	30.69
19	33.40	9.90	3.20	49.30	41.00	46.00	M25*1.6g	35.15	33.86
21	36.50	9.90	3.20	52.70	45.00	49.20	M25*1.6g	38.29	37.06
23	39.70	9.90	3.20	55.90	50.00	52.40	M34*1.6g	41.50	40.24
25	42.80	9.90	3.20	59.00	51.23	55.60	M37*1.6g	44.68	43.41

Резьбовой панельный разъем с гайкой для монтажа на стену

## Коммерческая информация

Код продажи продукта	<b>934WJ90SC</b>
Единица Упаковки	<b>1 шт.</b>

## Техническая информация

PRODUCT FEATURES	
Continuous Operating Temperature max.	<b>175 °C</b>
Continuous Operating Temperature min.	<b>65 °C</b>
Features	<b>MIL-DTL-38999</b>
Connector Type	<b>Screwed Socket</b>
Housing Size	<b>25(J)</b>
Number Of Contacts	<b>46 Ad.</b>
Placement	<b>j-90</b>
Housing Material	<b>Aluminium</b>
Housing Color	<b>Khaki Green</b>
Housing Coating	<b>Cadmium</b>
Contact Type	<b>Socket (40#20) (4#16) (2#8 Twinax)</b>
Wire Gauge	<b>24,22,20,18,16 AWG</b>
Contact Material	<b>Au/Cu</b>
Ingress Protection	<b>IP67</b>
Sealing Material	<b>Silicon</b>
Emi Shielding	<b>+</b>

Mating Cycles	<b>500</b>
Polarization	<b>C</b>
Service Rating	<b>I</b>

## **ELECTRICAL FEATURES**

Nominal Current	<b>7,5-13 A</b>
Operating Voltage Ac V Rms Max	<b>1800V AC/DC</b>

---