



ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ >
СИГНАЛЬНЫЕ ПАНЕЛИ (АННУНЦИАТОРЫ)

ANC-32 (110V AC/DC, 85- 300V AC/ DC p.s.) - ANC-32 (110V AC/DC, 85-300V AC/DC п.с.)

Артикул (SKU): 604672

Индикатор тревоги

Коммерческая информация

Код продажи продукта	604672
Единица Упаковки	1 шт.
Номер таможенного тарифа	853180709000
Вес за единицу, включая упаковку	540g kg.

Техническая информация

General	
Connection Type	Screw terminal
Time Interval	0,2,5,10,15,20,25,30 adjustable
Integrated Buttons	4 (Horn, Ack, Delete, Test)
Siren	+
Real Time Data Recording	6080 logs
Battery Life	> 5 years
Protection Class	IP20
Weight G	540
Packaging Quantity	1
Diagrams	---
DIMENSIONS	---

Power Supply

Voltage	<5W DC / <10VA AC
Frequency	45-65Hz

Environmental Conditions

Operating Temperature	-20°C +60°C
Storage Temperature	-40°C +75°C
Relative Humidity Non Condensing	Max.95% (no condensation)

Communication

Protocol	Modbus RTU
Baud Rate	1200-57600
Parity	
Stop Bit	
Slave Id	
Isolation	2500Vrms

Input Signal

Voltage	110V AC / DC
Frequency	45-65Hz
Quantity	32
Response Time	25±10ms

Output Connections

Output Type	Relay
Number of Connections	2
Type	1 NO (SPST)
Max Values Ac	5A/277V;1385VA
Max Values Dc	5A/30VDC;150W
Mechanical Operating Life	=10⁸ operation
Electrical Operating Life No Side	1x10⁵(5A@250VAC)

Window

Quantity	32
Color	Red / Green selectable
Size Mm	15,3 x 11,9
Illumination	With 2 pcs. red leds or 2 pcs. green led
Fast Flashing	180 Flash / Min
Slow Flashing	60 Flash / Min.
Marking	Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.

DIMENSIONS

Frontoverall Dimensions Height Mm	144
Frontoverall Dimensions Width Mm	144
Panel Cutout Dimensions Height Mm	
Panel Cutout Dimensions Width Mm	
Panel Cutout Dimensions Depth Mm	