

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ >  
АНАЛИЗАТОРЫ ЭНЕРГИИ

## POWYS 400R

Артикул (SKU): 606600

3Ø анализатор энергии

### Коммерческая информация

Код продажи продукта	<b>606600</b>
Единица Упаковки	<b>1 шт.</b>
Номер таможенного тарифа	<b>903032009011</b>

### Техническая информация

General	
Lcd Screen	-
Language Support	-
Password Protection	+
Networks	<b>TT, TN, IT</b>
Signal Waveforms	-
Connection Type	<b>3P4W, 3P3W</b>
Battery	-
Real Time Clock	-
Demand Period	<b>1-60 min. adjustable.</b>
Packaging Quantity	<b>1</b>
Seven Segment Display	
Without Screen	+
Minmax Data	+
Demand Data	+
Ghost Screen	

Phasor Diagram Display	
Screen Refresh Period	
Number Of Samples In The Period	

### Energy Measurement

3 Phase Energy Measurement	<b>+</b>
Number Of Tariffs	<b>1</b>
Number Of Sub Tariffs	
1 Energy Measurement	<b>+</b>
Number Of Reactive Measurement Zones	<b>4</b>

### Current Measurement Input

Measuring Range	<b>50mA-6A AC</b>
Overvoltage Category	<b>300 V Cat II</b>
Voltage Fluctuation Measurement	<b>2 kV</b>
Power Consumption	<b>&lt;0.2 VA</b>
Intermittent Overload	<b>100 A for 1 sec</b>
Sampling Frequency Between 45 65 Hz	

### Voltage Measurement Input

Overvoltage Category	<b>300 V Cat III</b>
Measuring Range L N	<b>10-300 Vrms</b>
Measuring Range L L	<b>17-500 Vrms</b>
Frequency Measuring Range	<b>45-65 Hz</b>
Power Consumption	<b>&lt;0.1 VA</b>
Sampling Frequency Between 45 65 Hz	

### Power Quality Measurements

Harmonic Measurement Current And Voltage	
Thdi	
Thdv	

### Measuring Accuracy Iec 61557 12

Total Active Power	<b>Class 1</b>
Total Reactive Power	<b>Class 1</b>
Total Reactive Energy	<b>Class 2</b>
Frequency	<b>Class 0.2</b>
Current	<b>Class 0.5</b>
Neutral Current	<b>Class 0.5</b>
Voltage	<b>Class 0.5</b>
Power Factor	<b>Class 0.2</b>
Thdv Thdi	<b>Class 1</b>
Total Apparent Power	<b>Class 1</b>
Total Active Energy	<b>Class 1</b>

### Measuring Accuracy Iec 62053 22

Total Active Energy	<b>Class 1</b>
---------------------	----------------

### Measuring Accuracy Iec 62053 23

Total Reactive Energy	<b>Class 1</b>
-----------------------	----------------

### Alarm Relay Outputs

Number Of Outputs	
Max Switching Current	
Max Switching Voltage	
Max Switching Power	

### Power Supply

Voltage	<b>85-300V AC / 85-300V DC</b>
Frequency	<b>45-65Hz</b>
Consumption	<b>&lt;3VA AC / &lt;2.5W DC</b>

### Mechanical Properties

Weight G	
Protection Class	<b>IP20</b>
Mounting Type	<b>Rail Mount</b>

## Environmental Conditions

Operating Temperature	<b>-20°C +70°C</b>
Storage Temperature	<b>-30°C +80°C</b>
Relative Humidity Non Condensing	<b>Max. 95% (no condensation)</b>

## Communication

Protocol	<b>Modbus RTU</b>
Baud Rate	<b>1200-57600</b>
Parity	<b>Odd, Even, None</b>
Stop Bit	<b>1</b>
Slave Id	<b>1-247</b>
Isolation	<b>2750V RMS</b>

## Time Recorded Data Storage

Hourly Records	
Daily Records	
Monthly Records	
Demand	
Alarm Records	<b>50</b>

## Digital Output

Isolation Level	<b>3750 Vrms</b>
Number Of Outputs	<b>2</b>
Voltage Switching Range	<b>Transistor</b>
Minimum Switching Frequency	<b>5-30 VDC</b>

## Digital Input

Number Of Inputs	<b>2</b>
Isolation Level	<b>3750 Vrms</b>
Minimum Counting Frequency	<b>100 Hz, 10 ms</b>
Input Type	<b>Dry Contact</b>

## Ethernet Interface

Protocol	
Port	
Gateway Feature	
Performance	

### Analog Output

Output Ranges 0.5 V, 0.10 V, 5.5 V, 10.10V, 0.20 Ma, 4.20 Ma	
Isolation	

### Other Measurements

Operating Time Counter	
Open Time Counter	
Power Failure Counter	

### Basic Electrical Measurements

Current	+
Voltage	+
Frequency	+
Active Power	+
Reactive Power	+
Apparent Power	+
Power Factor	+
Cos	+

### Cable Cross Sections Power Supply Voltage Relay

multi-core	<b>2.5mm<sup>2</sup> - 14AWG</b>
Single Core	<b>4mm<sup>2</sup> - 12AWG, 2x1.5mm<sup>2</sup> - 2x16AWG</b>

### Cable Cross Sections Current

multi-core	<b>2.5mm<sup>2</sup> - 14AWG</b>
Single Core	<b>4mm<sup>2</sup> - 12AWG, 2x1.5mm<sup>2</sup> - 2x16AWG</b>

### Cable Cross Sections Digital Input/output Rs485 Analog Output

multi-core	<b>2.5mm<sup>2</sup> - 14AWG</b>
------------	----------------------------------

Single Core

**4mm<sup>2</sup> - 12AWG, 2x1.5mm<sup>2</sup> - 2x16AWG**

---