

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > УДАЛЁННЫЙ ВВОД/ВЫВОД > МНОГОКАНАЛЬНЫЙ



## EASION 2M-1LL11-D

Артикул (SKU): 260016

Удаленный I/O

### Коммерческая информация

Код продажи продукта	<b>260016</b>
Единица Упаковки	<b>1 шт.</b>
Номер таможенного тарифа	<b>853710980019</b>

### Техническая информация

#### General

Case Width Mm	<b>(95mmx160mm)x58mm</b>
Mounting Type	<b>Rail Mount</b>

#### Power Supply

Voltage	<b>24 - 50 V AC / 12 - 50 V DC</b>
Frequency	<b>45-65 Hz</b>
Consumption	<b>&lt;13VA AC / &lt;7W</b>

#### Mechanical Properties

Weight G	
Packaging Quantity	<b>1</b>

#### Environmental Conditions

Operating Temperature	<b>-20 to +70 °C</b>
Storage Temperature	<b>-20°C..+70°C</b>
Relative Humidity Non Condensing	<b>Max.95% (no condensation)</b>

## Digital Output

Number Of Outputs	<b>12</b>
Switching Current Voltage	<b>50mA / 5-30V DC</b>
Response Time	<b>&lt;18µs</b>

## Relay Output

Number Of Outputs	
Max Switching Current Voltage Power	

## Input Dry Contact

Number Of Inputs	<b>12</b>
------------------	-----------

## Inputs Wet Contact

Number Of Inputs	
Input Voltage	
Input Current	
Frequency	
Isolation Level	

## Communication Rs485 Modbus Rtu

Baud Rate	<b>1200 .. 115200</b>
Stop Bit	<b>1,2</b>
Slave Id	<b>1 ..247</b>

## Communication Micro Usb Modbus Rtu

Baud Rate	-
Stop Bit	-
Slave Id	-

## Communication Http Rest

Interface	
Baud Rate	

## Communication Modbus Tcp

Interface

### Communication Mqtt Http Rest

Interface

### Communication Rs232 Modbus Rtu

Baud Rate	<b>1200 .. 115200</b>
-----------	-----------------------

Stop Bit	<b>1,2</b>
----------	------------

Slave Id	<b>1 ..247</b>
----------	----------------