

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > УДАЛЁННЫЙ ВВОД/ВЫВОД > МНОГОКАНАЛЬНЫЙ



EASION 5M-1Z111

Артикул (SKU): 260301

Удаленный I/O

Коммерческая информация

Код продажи продукта	260301
Единица Упаковки	1 шт.
Номер таможенного тарифа	853710980019

Техническая информация

General	
Case Width Mm	(95mmx160mm)x58mm
Mounting Type	Rail Mount
Power Supply	
Voltage	24 - 50 V AC / 12 - 50 V DC
Frequency	45-65 Hz
Consumption	<13VA AC / <7W
Mechanical Properties	
Weight G	
Packaging Quantity	1
Environmental Conditions	
Operating Temperature	-20 to +70 °C
Storage Temperature	-20°C..+70°C

Relative Humidity Non Condensing

Max.95% (no condensation)

Digital Output

Number Of Outputs

Switching Current Voltage

Response Time

Relay Output

Number Of Outputs

Max Switching Current Voltage Power

Input Dry Contact

Number Of Inputs

Inputs Wet Contact

Number Of Inputs

24

Input Voltage

12 - 230 V AC/DC

Input Current

1 mA at 5V AC/DC-2,5 mA at 24V AC/DC-4 mA at 230V AC/DC

Frequency

45-65 Hz

Isolation Level

5000Vrms optical insulation

Communication Rs485 Modbus Rtu

Baud Rate

Stop Bit

Slave Id

Communication Micro Usb Modbus Rtu

Baud Rate

Stop Bit

Slave Id

Communication Http Rest

Interface

Micro USB

Baud Rate

38400

Communication Modbus Tcp

Interface	+
-----------	---

Communication Mqtt Http Rest

Interface	Ethernet 10/100 Base - TX
-----------	----------------------------------

Communication Rs232 Modbus Rtu

Baud Rate	1200 .. 115200
-----------	-----------------------

Stop Bit	1,2
----------	------------

Slave Id	1 ..247
----------	----------------
