


КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ТРАНСФОРМАТОРНЫЕ  
КЛЕММНЫЕ БЛОКИ

## TRV 10 Бежевый

Артикул (SKU): 422030

Винтовые трансформаторные клеммы 10 мм<sup>2</sup>

### Коммерческая информация

Код продажи продукта	<b>422030</b>
Единица Упаковки	<b>25 шт.</b>
Номер таможенного тарифа	<b>853690950000</b>
Вес за единицу, включая упаковку	<b>0.03644 kg.</b>

### Техническая информация

#### PRODUCT FEATURES

Number of Connections	<b>4</b>
Color	<b>Beige</b>
Number of Levels	<b>1</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Impulse Voltage Category	<b>III</b>
Insulation Material Group	<b>I</b>
Pollution Degree	<b>3</b>
Connection According to Standard	<b>IEC60998-1 / 61558-1</b>
Continuous Operating Temperature max.	<b>120 °C</b>
Continuous Operating Temperature min.	<b>-55 °C</b>

#### ELECTRICAL FEATURES

Nominal Impulse Voltage	<b>8 Kv</b>
-------------------------	-------------

Nominal Current	<b>63 A</b>
Nominal Voltage	<b>750 V</b>
Maximum Load Current	<b>63 A</b>

## CONNECTION DATA

Connection Type	<b>Screw Connection</b>
Single-core min. conductor cross-section	<b>0,5 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>16 mm<sup>2</sup></b>
Conductor Cross Section Awgkcmil Min	<b>20 AWG</b>
Conductor Cross Section Awgkcmil Max	<b>6 AWG</b>
Multi-core min. conductor cross-section	<b>0,5 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>16 mm<sup>2</sup></b>
Multi-core min. conductor cross-section with ferrule	<b>0,5 mm<sup>2</sup></b>
Multi-core max. conductor cross-section with ferrule	<b>10 mm<sup>2</sup></b>
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	<b>0,5 mm<sup>2</sup></b>
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	<b>6 mm<sup>2</sup></b>
Min. Stripping Length	<b>11 mm</b>
Max. Stripping Length	<b>12 mm</b>
Internal cylindrical indicator	<b>B6</b>
Tightening Torque Min	<b>1,2 Nm</b>
Tightening Torque Max	<b>1,8 Nm</b>

## DIMENSIONS

Width	<b>22 mm</b>
Length	<b>35,80 mm</b>
Height	<b>46,00 mm</b>