

КЛЕММНЫЕ БЛОКИ > КЛЕММНЫЕ КОЛОДКИ С ВСТАВНЫМ КРЕПЛЕНИЕМ > МНОГОПРОВОДНЫЕ КЛЕММНЫЕ БЛОКИ

PRD 1E Бежевый

Артикул (SKU): 328010

Push-In с оранжевой кнопкой, 1 мм² 1 вход-2 выход проходная

Коммерческая информация

| | |
|--------------------------|---------------------|
| Код продажи продукта | 328010 |
| Единица Упаковки | 50 шт. |
| Номер таможенного тарифа | 853690950000 |

Техническая информация

| PRODUCT FEATURES | |
|---------------------------------------|----------------------|
| Number of Connections | 3 |
| Color | Beige |
| Number of Levels | 1 |
| Insulation Material | PA |
| UL 94 Flammability Class | V0 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-1 |
| Continuous Operating Temperature max. | 130 °C |
| Continuous Operating Temperature min. | -60 °C |

| ELECTRICAL FEATURES | |
|-------------------------|---------------|
| Nominal Impulse Voltage | 8 Kv |
| Nominal Current | 13,5 A |

| | |
|----------------------|---------------|
| Nominal Voltage | 800 V |
| Maximum Load Current | 17,5 A |

CONNECTION DATA

| | |
|--|----------------------------|
| Connection Type | Push-In Connection |
| Single-core min. conductor cross-section | 0,08 mm² |
| Single-core max. conductor cross-section | 1,5 mm² |
| Conductor Cross Section Awgkcmil Min | 28 AWG |
| Conductor Cross Section Awgkcmil Max | 16 AWG |
| Multi-core min. conductor cross-section | 0,14 mm² |
| Multi-core max. conductor cross-section | 1,5 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,14 mm² |
| Multi-core max. conductor cross-section with ferrule | 1 mm² |
| Min. Stripping Length | 8 mm |
| Max. Stripping Length | 10 mm |
| Internal cylindrical indicator | A1/B1 |

DIMENSIONS

| | |
|-----------------|-----------------|
| Width | 3,6 mm |
| Length | 65,20 mm |
| Height Mr 35X75 | 37,30 mm |
| Height MR 35x15 | 44,80 mm |