



КЛЕММНЫЕ БЛОКИ > КЛЕММНЫЕ КОЛОДКИ С ВСТАВНЫМ КРЕПЛЕНИЕМ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

PRD 1ET Жёлто/Зелёный

Артикул (SKU): 337590

Клеммная колодка push-in с оранжевой кнопкой, 1 мм² 1 вход-2 выхода заземляющая

Коммерческая информация

Код продажи продукта	337590
Единица Упаковки	50 шт.
Номер таможенного тарифа	853690950000

Техническая информация

PRODUCT FEATURES	
Number of Connections	3
Color	Yellow/Green
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Protective Conductor Type	PE
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL1 - HL2 - HL3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Push-In Connection
-----------------	---------------------------

Single-core min. conductor cross-section	0,08 mm²
--	----------------------------

Single-core max. conductor cross-section	1,5 mm²
--	---------------------------

Conductor Cross Section Awgkcmil Min	28 AWG
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	0,16 AWG
--------------------------------------	-----------------

Multi-core min. conductor cross-section	0,14 mm²
---	----------------------------

Multi-core max. conductor cross-section	1,5 mm²
---	---------------------------

Multi-core min. conductor cross-section with ferrule	0,14 mm²
--	----------------------------

Multi-core max. conductor cross-section with ferrule	1 mm²
--	-------------------------

Min. Stripping Length	8 mm
-----------------------	-------------

Max. Stripping Length	10 mm
-----------------------	--------------

Internal cylindrical indicator	A1/B1
--------------------------------	--------------

Conductor Cross Section Stranded Ferrule Without Plastic Sleeve Max	1,5 mm²
---	---------------------------

DIMENSIONS

Width	3,6 mm
-------	---------------

Length	65,20 mm
--------	-----------------

Height Mr 35X75	37,30 mm
-----------------	-----------------

Height MR 35x15	44,80 mm
-----------------	-----------------