



КЛЕММНЫЕ БЛОКИ > КЛЕММНЫЕ КОЛОДКИ С ВСТАВНЫМ КРЕПЛЕНИЕМ > ПРОХОДНЫЕ КЛЕММЫ

PRD 6 Серый

Артикул (SKU): 329589

Клеммная колодка push-in с оранжевой кнопкой, 6 мм² проходная

Коммерческая информация

Код продажи продукта	329589
Единица Упаковки	50 шт.
Номер таможенного тарифа	853690950000

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C
ELECTRICAL FEATURES	
Nominal Impulse Voltage	8 Kv
Nominal Current	41 A

Nominal Voltage	1000 V
Maximum Load Current	57 A

CONNECTION DATA

Connection Type	Push-In Connection
Single-core min. conductor cross-section	0,2 mm²
Single-core max. conductor cross-section	10 mm²
Conductor Cross Section Awgkcmil Min	24 AWG
Conductor Cross Section Awgkcmil Max	8 AWG
Multi-core min. conductor cross-section	0,2 mm²
Multi-core max. conductor cross-section	6 mm²
Min. Stripping Length	10 mm
Max. Stripping Length	12 mm
Internal cylindrical indicator	A5

DIMENSIONS

Width	8 mm
Length	69,3 mm
Height Mr 35X75	39,45 mm
Height MR 35x15	46,95 mm