

КЛЕММНЫЕ БЛОКИ > КЛЕММНЫЕ КОЛОДКИ С ВСТАВНЫМ КРЕПЛЕНИЕМ >
КЛЕММЫ ДЛЯ ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

РҮК 2,5CD-A Серый

Артикул (SKU): 307449

Клеммная колодка push-in 2,5 мм², четырехполюсная диодная переходная

Коммерческая информация

Код продажи продукта	307449
Единица Упаковки	50 шт.
Номер таможенного тарифа	853630300000

Техническая информация

PRODUCT FEATURES	
Number of Connections	4
Color	
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
Note	
ELECTRICAL FEATURES	
Nominal Impulse Voltage	8 Kv

Nominal Current	0,5 A
Nominal Voltage	800 V

CONNECTION DATA

Connection Type	Push-In Baglanti
Single-core min. conductor cross-section	0,34 mm²
Single-core max. conductor cross-section	4 mm²
Conductor Cross Section Awgkcmil Min	22 AWG
Conductor Cross Section Awgkcmil Max	12 AWG
Multi-core min. conductor cross-section	0,34 mm²
Multi-core max. conductor cross-section	2,5 mm²
Multi-core min. conductor cross-section with ferrule	0,25 mm²
Multi-core max. conductor cross-section with ferrule	2,5 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,5 mm²
Min. Stripping Length	9 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A3

DIMENSIONS

Width	5 mm
Length	76,4 mm
Height Mr 35X75	43 mm
Height MR 35x15	50,5 mm