

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ >  
СИГНАЛЬНЫЕ ПАНЕЛИ (АННУНЦИАТОРЫ)



## LSK-9(24VAC/DC)

Артикул (SKU): 583091

Цифровой индикатор тревоги

### Коммерческая информация

|                                  |                     |
|----------------------------------|---------------------|
| Код продажи продукта             | <b>583091</b>       |
| Единица Упаковки                 | <b>1 шт.</b>        |
| Номер таможенного тарифа         | <b>853649000029</b> |
| Вес за единицу, включая упаковку | <b>222g kg.</b>     |

### Техническая информация

| General                  |                                |
|--------------------------|--------------------------------|
| Connection Type          | <b>Screw terminal</b>          |
| Time Interval            | ---                            |
| Integrated Buttons       | ---                            |
| Siren                    | ---                            |
| Real Time Data Recording | ---                            |
| Battery Life             | ---                            |
| Protection Class         | <b>IP50 (front)IP20 (back)</b> |
| Weight G                 | <b>222</b>                     |
| Packaging Quantity       | <b>1</b>                       |
| Diagrams                 | ---                            |
| DIMENSIONS               | ---                            |
| Power Supply             |                                |
| Voltage                  | ---                            |

|           |     |
|-----------|-----|
| Frequency | --- |
|-----------|-----|

### Environmental Conditions

|                                  |                    |
|----------------------------------|--------------------|
| Operating Temperature            | <b>-20°C +70°C</b> |
| Storage Temperature              | <b>-30°C +80°C</b> |
| Relative Humidity Non Condensing | <b>Max. 95%</b>    |

### Communication

|           |     |
|-----------|-----|
| Protocol  | --- |
| Baud Rate | --- |
| Parity    | --- |
| Stop Bit  |     |
| Slave Id  |     |
| Isolation |     |

### Input Signal

|               |   |
|---------------|---|
| Voltage       | <b>24V AC / DC</b>  |
| Frequency     | <b>Min. 45 Hz (for AC signal input)Min. 45 Hz (for AC signal input)</b> |
| Quantity      | <b>9</b>  |
| Response Time | <b>Maks. 10ms</b>   |

### Output Connections

|                                   |  |
|-----------------------------------|--|
| Output Type                       |  |
| Number of Connections             |  |
| Type                              |  |
| Max Values Ac                     |  |
| Max Values Dc                     |  |
| Mechanical Operating Life         |  |
| Electrical Operating Life No Side |  |

### Window

|          |            |
|----------|------------|
| Quantity | <b>9</b>   |
| Color    | <b>Red</b> |

|               |  |
|---------------|--|
| Size Mm       | <b>20.9x18.7</b>   |
| Illumination  | <b>6 x Red LED</b>   |
| Fast Flashing |  |
| Slow Flashing |  |
| Marking       | <b>Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.</b> |

## **DIMENSIONS**

|                                   |              |
|-----------------------------------|--------------|
| Frontoverall Dimensions Height Mm | <b>96</b>    |
| Frontoverall Dimensions Width Mm  | <b>96</b>    |
| Panel Cutout Dimensions Height Mm | <b>89,5</b>  |
| Panel Cutout Dimensions Width Mm  | <b>89,5</b>  |
| Panel Cutout Dimensions Depth Mm  | <b>66,66</b> |