



ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ > СЧЁТЧИКИ ЭЛЕКТРОЭНЕРГИИ

## 180-0W-01

Артикул (SKU): 606372

1Ø счетчик энергии

### Коммерческая информация

Код продажи продукта	<b>606372</b>
Единица Упаковки	<b>1 шт.</b>
Номер таможенного тарифа	<b>903032009011</b>
Вес за единицу, включая упаковку	<b>0.12 kg.</b>

### Техническая информация

General	
Connection Type	<b>1P2W</b>
Real Time Clock	
Current Connection Type	<b>Direkt Baglantili (45A ya kadar)</b>
Alarm	<b>+</b>
Energy Measurement	
Number Of Tariffs	<b>1</b>
Number Of Sub Tariffs	
Number Of Reactive Measurement Zones	
Energy Measurement Type	<b>Import kWh</b>
Partial Counter	
Balance Energy	

### Current Measurement Input

Measuring Range	<b>0,25 .. 80A</b>
-----------------	--------------------

### Voltage Measurement Input

Measuring Range L N	<b>100-300V AC</b>
---------------------	--------------------

Measuring Range L L	-
---------------------	---

### Power Quality Measurements

Harmonic Measurement Current And Voltage	<b>31</b>
--	-----------

Thdi	+
------	---

Thdv	+
------	---

### Power Supply

Voltage	<b>100-300V AC</b>
---------	--------------------

Frequency	<b>45-65Hz</b>
-----------	----------------

Consumption	<b>&lt;3VA AC</b>
-------------	-------------------

### Mechanical Properties

Weight G	<b>120</b>
----------	------------

Protection Class	<b>IP20</b>
------------------	-------------

Mounting Type	<b>Rail Mount</b>
---------------	-------------------

### Environmental Conditions

Operating Temperature	<b>-25°C +50°C</b>
-----------------------	--------------------

Storage Temperature	<b>-25°C +70°C</b>
---------------------	--------------------

Relative Humidity Non Condensing	<b>Max. 80% (no condensation)</b>
----------------------------------	-----------------------------------

### Communication

Protocol	
----------	--

Baud Rate	
-----------	--

Parity	
--------	--

Stop Bit	
----------	--

Slave Id	
----------	--

Isolation	
-----------	--

## Digital Output

Frequency	<b>5-30 VDC</b>
Number Of Inputs	<b>1 (sabit)</b>
Switched Voltage Range	<b>Transistor</b>
Isolation	<b>3750 Vrms</b>

## Digital Input

Number Of Inputs	
Input Type	
Isolation	

## Other Measurements

Operating Time Counter	
Open Time Counter	
Power Failure Counter	

## Basic Electrical Measurements

Current	<b>+</b>
Voltage	<b>+</b>
Frequency	<b>+</b>
Active Power	<b>+</b>
Reactive Power	<b>+</b>
Apparent Power	<b>+</b>

## Cable Cross Sections Power Supply Voltage Relay

multi-core	
Single Core	

## Cable Cross Sections Current

multi-core	
Single Core	

## Cable Cross Sections Digital Inputoutput Rs485 Analog Output

multi-core	
------------	--

Single Core

### Measurement Class

En 50470

62053 21

**Class 1**

### Measurement

Max Min Data

Demand

### Led Impulse

Kwh

+

Kvarh

+