



ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ > СЧЁТЧИКИ ЭЛЕКТРОЭНЕРГИИ

580-1M-V3

Артикул (SKU): 606373

1Ø счетчик энергии

Коммерческая информация

Код продажи продукта	606373
Единица Упаковки	1 шт.
Номер таможенного тарифа	903032009011
Вес за единицу, включая упаковку	0.12 kg.

Техническая информация

General	
Connection Type	1P2W
Real Time Clock	+
Current Connection Type	Direkt Baglantili (45A ya kadar)
Alarm	+
Energy Measurement	
Number Of Tariffs	2
Number Of Sub Tariffs	4
Number Of Reactive Measurement Zones	2
Energy Measurement Type	Import & Export kWh-kVArh
Partial Counter	
Balance Energy	

Current Measurement Input

Measuring Range	0,15 .. 80A
-----------------	--------------------

Voltage Measurement Input

Measuring Range L N	100-300V AC
---------------------	--------------------

Measuring Range L L	-
---------------------	---

Power Quality Measurements

Harmonic Measurement Current And Voltage	31
--	-----------

Thdi	+
------	----------

Thdv	+
------	----------

Power Supply

Voltage	100-300V AC
---------	--------------------

Frequency	45-65Hz
-----------	----------------

Consumption	<3VA AC
-------------	-------------------

Mechanical Properties

Weight G	120
----------	------------

Protection Class	IP20
------------------	-------------

Mounting Type	Rail Mount
---------------	-------------------

Environmental Conditions

Operating Temperature	-25°C +50°C
-----------------------	--------------------

Storage Temperature	-25°C +70°C
---------------------	--------------------

Relative Humidity Non Condensing	Max. 80% (no condensation)
----------------------------------	-----------------------------------

Communication

Protocol	Modbus RTU
----------	-------------------

Baud Rate	1200-115200
-----------	--------------------

Parity	Odd, Even, None
--------	------------------------

Stop Bit	1
----------	----------

Slave Id	1-247
----------	--------------

Isolation	2750V RMS
-----------	------------------

Digital Output

Frequency	5-30 VDC
-----------	-----------------

Number Of Inputs	2 (Ayarlanabilir)
------------------	--------------------------

Switched Voltage Range	Transistor
------------------------	-------------------

Isolation	3750 Vrms
-----------	------------------

Digital Input

Number Of Inputs	
------------------	--

Input Type	
------------	--

Isolation	
-----------	--

Other Measurements

Operating Time Counter	
------------------------	--

Open Time Counter	
-------------------	--

Power Failure Counter	
-----------------------	--

Basic Electrical Measurements

Current	+
---------	----------

Voltage	+
---------	----------

Frequency	+
-----------	----------

Active Power	+
--------------	----------

Reactive Power	+
----------------	----------

Apparent Power	+
----------------	----------

Cable Cross Sections Power Supply Voltage Relay

multi-core	
------------	--

Single Core	
-------------	--

Cable Cross Sections Current

multi-core	
------------	--

Single Core	
-------------	--

Cable Cross Sections Digital Inputoutput Rs485 Analog Output

multi-core	
------------	--

Single Core

Measurement Class

En 50470

62053 21

Class 1

Measurement

Max Min Data

Demand

Led Impulse

Kwh

+

Kvarh

+