

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > РЕЛЕ ЗАЩИТЫ И УПРАВЛЕНИЯ > РЕЛЕ ВРЕМЕНИ



MEASTRO 122

Артикул (SKU): 270705

Астрономическое реле времени

Коммерческая информация

Код продажи продукта	270705
Единица Упаковки	1 шт.
Номер таможенного тарифа	853649000029
Вес за единицу, включая упаковку	0.2 kg.

Техническая информация

General	
Lcd Screen	+
Connection Type	Screw terminal
Protection Class	IP20
Case Width Mm	36 mm
Mounting Type	Rail Mount
Supply Frequency	50-60Hz
Output Type	Relay
Screen Size	1,5 "
Screen Refresh Time	0,5 sn
Number Of Programs	100
Infrared Distance	550 mm

Truth	±1sec/day
Battery Reserve Time	7 Yil / Years

Power Supply

Voltage	180...265 V AC
Frequency	35-70Hz
Power Consumption	<11VA AC

Environmental Conditions

Operating Temperature	-20°C..+70 °C
Storage Temperature	-30°C..+80 °C
Relative Humidity Non Condensing	90% non-condensing

Communication

Protocol	Modbus RTU (RS485)
Baud Rate	1200 .. 115200
Slave Id	1 .. 247

Relay Output

Number Of Outputs	1
Max Switching Current	16A / 250VAC
Max Switching Power	1250VA
Type	2 C/O (SPDT)
Electrical Life	5x10⁴
Mechanical Life	= 10⁷