



КЛЕММНЫЕ БЛОКИ > КЛЕММНЫЕ КОЛОДКИ С ВСТАВНЫМ КРЕПЛЕНИЕМ > ПРОХОДНЫЕ КЛЕММЫ

MPB 4-5

Артикул (SKU): 425550

NULL

Коммерческая информация

Код продажи продукта	425550
Единица Упаковки	30 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.0066 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Transparent
Number of Levels	1
Insulation Material	PC
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC EN 60664
Continuous Operating Temperature max.	105 °C
Continuous Operating Temperature min.	-45 °C

ELECTRICAL FEATURES	
Nominal Impulse Voltage	4 Kv

Nominal Current	32 A (4 mm² için) / 32 A (at 4 mm²) A
Nominal Voltage	450 V
Maximum Load Current	41 A (with 6 mm² conductor cross section) A

CONNECTION DATA

Connection Type	Push-In
Single-core min. conductor cross-section	0,75 mm²
Single-core max. conductor cross-section	6 mm²
Conductor Cross Section Awgkcmil Min	18 AWG
Conductor Cross Section Awgkcmil Max	10 AWG
Multi-core min. conductor cross-section	0,75 mm²
Multi-core max. conductor cross-section	4 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	2,5 mm²
Min. Stripping Length	11 mm
Max. Stripping Length	11 mm
Internal cylindrical indicator	A3

DIMENSIONS

Width	36,3 mm
Length	17,7 mm
Height	12 mm