



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ПРЕДОХРАНИТЕЛЬНЫЕ КЛЕММЫ

AVK 4 FSTLD/NM 24V (Без полярности) (Серый)

Артикул (SKU): 314129

4мм² Винтовой 3-уровневый клеммник фаза + предохранитель + LED заземление

Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 314129 |
| Единица Упаковки | 30 шт. |
| Номер таможенного тарифа | 853690950000 |
| Вес за единицу, включая упаковку | 0.03466 kg. |

Техническая информация

| PRODUCT FEATURES | |
|---------------------------------------|--|
| Number of Connections | 5 |
| Color | Grey |
| Number of Levels | 3 |
| Insulation Material | PA |
| UL 94 Flammability Class | V0 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-1 / IEC 60947-7-2 / IEC 60947-7-3 |
| Continuous Operating Temperature max. | 130 °C |
| Continuous Operating Temperature min. | -60 °C |
| Fuse | G / 5x20 - 5x25 |

| | |
|-----------|--------------|
| Fuse Type | Glass |
|-----------|--------------|

ELECTRICAL FEATURES

| | |
|-------------------------|--------------------------|
| Nominal Impulse Voltage | 6 Kv |
| Nominal Current | 32 A |
| Nominal Voltage | 24 V (Fuse) 500 V |

CONNECTION DATA

| | |
|--|---------------------------|
| Connection Type | Screw connection |
| Single-core min. conductor cross-section | 0,2 mm² |
| Single-core max. conductor cross-section | 6 mm² |
| Conductor Cross Section Awgkcmil Min | 24 AWG |
| Conductor Cross Section Awgkcmil Max | 10 AWG |
| Multi-core min. conductor cross-section | 0,2 mm² |
| Multi-core max. conductor cross-section | 6 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,2 mm² |
| Multi-core max. conductor cross-section with ferrule | 4 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | 0,5 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | 2,5 mm² |
| Min. Stripping Length | 8 mm |
| Max. Stripping Length | 9 mm |
| Internal cylindrical indicator | A4 |
| Tightening Torque Min | 0,5 Nm |
| Tightening Torque Max | 0,8 Nm |

DIMENSIONS

| | |
|-----------------|----------------------|
| Width | 8 mm |
| Length | 89,30 mm |
| Height Mr 35X75 | 68,00 mm |
| Height MR 35x15 | 75,4575,45 mm |