



КЛЕММНЫЕ БЛОКИ > КЛЕММНЫЕ КОЛОДКИ С ВСТАВНЫМ КРЕПЛЕНИЕМ > КЛЕММЫ ДЛЯ ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

PRD 4_2FLD_220V AC/DC Серый

Артикул (SKU): 329279

4 мм² Двухуровневый 4-полюсный клеммник push-in с LED

Коммерческая информация

Код продажи продукта	329279
Единица Упаковки	50 шт.
Номер таможенного тарифа	853690950000

Техническая информация

PRODUCT FEATURES	
Number of Connections	4
Color	Grey
Number of Levels	2
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL1 - HL2 - HL3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C
Note	

ELECTRICAL FEATURES

Nominal Impulse Voltage	6 Kv
Nominal Current	32 A (at 4 mm²) A
Nominal Voltage	220 V
Maximum Load Current	41 A (with 6 mm² conductor cross section) A

CONNECTION DATA

Connection Type	Push-in connection
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	6 mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	10 AWG
Multi-core min. conductor cross-section	0,14 mm²
Multi-core max. conductor cross-section	4 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	4 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	1 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A4
Conductor Cross Section Stranded Ferrule Without Plastic Sleeve Max	mm²

DIMENSIONS

Width	6,2 mm
Length	89,70 mm
Height Mr 35X75	51,30 mm
Height MR 35x15	58,80 mm