

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ >
АНАЛИЗАТОРЫ ЭНЕРГИИ



POWYS 1110

Артикул (SKU): 606351

Энергетический анализатор 1Ø

Коммерческая информация

Код продажи продукта	606351
Единица Упаковки	1 шт.
Номер таможенного тарифа	902830900000
Вес за единицу, включая упаковку	0.14 kg.

Техническая информация

General	
Lcd Screen	
Language Support	
Password Protection	+
Voltage Transformer Ratio Vtr	1 - 5000
Current Transformer Ratio Ctr	1 - 5000
Number Of Measurements In One Period	256
Lcdscreen Refresh Rate	1 sn.
Networks	TT, TN, IT
Signal Waveforms	
Connection Type	1 Faz (1 akım trafosu ve nötr ile)
Battery	

Real Time Clock	
Four Quadrant Measurement	
Demand Period	1-60 min. adjustable
Phase Diagram	
Minmaxdemand Values	+
Protection Class	IP20
Mounting Type	Rail Mounted
Seven Segment Display	+

Energy Measurement

Multiple Sub Tariffs Peak On Peak And Off Peak	
1 Phase Energy Measurement	+
3 Phase Energy Measurement	
4 Quadrant Reactive Energy Measurement	
Number Of Tariffs	1

Current Measurement Input

Measuring Range	10mA - 6A AC
Overvoltage Category	300 V Cat II
Voltage Fluctuation Measurement	2 kV
Power Consumption	<0.2 VA
Intermittent Overload	100 A for 1 sec
Sampling Frequency Between 45 65 Hz	12,8 kHz

Voltage Measurement Input

Overvoltage Category	300 V Cat III
Measuring Range L N	10-500 Vrms
Measuring Range L L	
Frequency Measuring Range	45-65 Hz
Power Consumption	<0.1 VA
Sampling Frequency Between 45 65 Hz	12,8 kHz

Power Quality Measurements

Thd Voltage As	+
Thd Current As	+
Harmonics For Current And Voltage Phases	Up to 31st

Measuring Accuracy Iec 61557 12

Total Active Power	Class 0.5
Total Reactive Power	Class 1
Total Reactive Energy	Class 2
Frequency	Class 0.1
Current	Class 0.5
Neutral Current	Class 0.5
Voltage	Class 0.2
Power Factor	Class 0.5
Thdv Thdi	Class 1
Total Apparent Power	Class 0.5
Total Active Energy	Class 0.5

Measuring Accuracy Iec 62053 22

Total Active Energy	Class 0.5S
---------------------	-------------------

Measuring Accuracy Iec 62053 23

Total Reactive Energy	Class 2
-----------------------	----------------

Alarm Relay Outputs

Number Of Outputs	
Type	
Max Switching Current	
Max Switching Voltage	
Max Switching Power	

Power Supply

Voltage	85-300V AC / 85-300V DC
Frequency	45-65Hz

Consumption	<4VA AC
-------------	-------------------

Environmental Conditions

Operating Temperature	-20 to +70°C
Storage Temperature	-30°C +80°C
Relative Humidity Non Condensing	Maks. 95%

Communication

Protocol	Modbus RTU
Baud Rate	1200-57600 bps adjustable
Parity	Odd, Even, None
Stop Bit	1
Slave Id	1-247
Isolation	2750V RMS

Time Recorded Data Storage

Hourly Records	
Daily Records	
Monthly Records	
Demand	
Alarm Records	

Digital Output

Isolation Level	
Number Of Outputs	
Type	
Voltage Switching Range	
Minimum Switching Frequency	

Digital Input

Number Of Inputs	
Isolation Level	
Minimum Counting Frequency	

Input Type

Analog Output

Number Of Outputs

Output Ranges 0 5 V 0 10 V 5 5 V 10 10V 0 20
Ma 4 20 Ma

Isolation

Cable Cross Sections Power Supply Voltage Current Relay Outputs

Loaded

2.5mm² - 14AWG

Unloaded

4mm² - 12AWG, 2x1.5mm² - 2x16AWG

Cable Cross Sections Digital Io Rs485 Analog Outputs

Loaded

1.5mm² - 16AWG

Unloaded

1.5mm² - 16AWG, 2x0.75mm² - 2x18AWG