



КЛЕММНЫЕ БЛОКИ > КЛЕММНЫЕ КОЛОДКИ С ВСТАВНЫМ КРЕПЛЕНИЕМ > ПРОХОДНЫЕ КЛЕММЫ

PRD 16 Синий

Артикул (SKU): 329721

2-полюсная проходная клеммная колодка с push-in подключением 16 мм²

Коммерческая информация

Код продажи продукта	329721
Единица Упаковки	30 шт.
Номер таможенного тарифа	853690950000

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Mavi
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
Nominal Current	76 A (16 mm² için) A
Nominal Voltage	1000 V
Maximum Load Current	90 A (25 mm² iletken kesit alan?) A

CONNECTION DATA

Connection Type	Push-In Bağlantı
Single-core min. conductor cross-section	0,5 mm²
Single-core max. conductor cross-section	25 mm²
Conductor Cross Section Awgkcmil Min	20 AWG
Conductor Cross Section Awgkcmil Max	4 AWG
Multi-core min. conductor cross-section	0,5 mm²
Multi-core max. conductor cross-section	16 mm²
Min. Stripping Length	18 mm
Max. Stripping Length	20 mm
Internal cylindrical indicator	A7

DIMENSIONS

Width	12 mm
Length	76,80 mm
Height Mr 35X75	51,40 mm
Height MR 35x15	58,90 mm