



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ПРЕДОХРАНИТЕЛЬНЫЕ КЛЕММЫ

ASK 2LD-220VAC

Артикул (SKU): 351619

Винтовая предохранительная клемма 6 мм² с LED

Коммерческая информация

Код продажи продукта	351619
Единица Упаковки	25 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.01908 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-3
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
Fuse	G / 5x20 - 5x25
Fuse Type	Cam / Glass

ELECTRICAL FEATURES

Nominal Current **6.3 A**

Nominal Voltage **220 V**

CONNECTION DATA

Connection Type **Screw Connection**

Single-core min. conductor cross-section **0.2 mm²**

Single-core max. conductor cross-section **10 mm²**

Conductor Cross Section Awgkcmil Min **24 AWG**

Conductor Cross Section Awgkcmil Max **8 AWG**

Multi-core min. conductor cross-section **0.2 mm²**

Multi-core max. conductor cross-section **10 mm²**

Multi-core min. conductor cross-section with ferrule **0,25 mm²**

Multi-core max. conductor cross-section with ferrule **6 mm²**

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min **0,5 mm²**

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max **4 mm²**

Min. Stripping Length **10 mm**

Max. Stripping Length **12 mm**

Internal cylindrical indicator **B5**

Tightening Torque Min **0.8 Nm**

Tightening Torque Max **1.2 Nm**

DIMENSIONS

Width **8 mm**

Length **64.2 mm**

Height Mr 35X75 **45 mm**

Height MR 35x15 **52.5 mm**

Height Mr 32 **49.6 mm**