



КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ПРЕДОХРАНИТЕЛЬНЫЕ КЛЕММЫ

## ASK 5

Артикул (SKU): 353409

Винтовая предохранительная клемма 4 мм<sup>2</sup>

### Коммерческая информация

Код продажи продукта	<b>353409</b>
Единица Упаковки	<b>50 шт.</b>
Номер таможенного тарифа	<b>853690950000</b>
Вес за единицу, включая упаковку	<b>0.0176 kg.</b>

### Техническая информация

PRODUCT FEATURES	
Number of Connections	<b>2</b>
Color	<b>Grey</b>
Number of Levels	<b>1</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Impulse Voltage Category	<b>III</b>
Insulation Material Group	<b>I</b>
Pollution Degree	<b>3</b>
Connection According to Standard	<b>IEC 60947-7-3</b>
Continuous Operating Temperature max.	<b>120 °C</b>
Continuous Operating Temperature min.	<b>-55 °C</b>
Fuse	<b>G / 5x20 - 5x25</b>
Fuse Type	<b>Cam / Glass</b>

## ELECTRICAL FEATURES

Nominal Current	<b>10 A</b>
Nominal Voltage	<b>500 V</b>

## CONNECTION DATA

Connection Type	<b>Screw Connection</b>
-----------------	-------------------------

Single-core min. conductor cross-section	<b>0.2 mm<sup>2</sup></b>
--	---------------------------

Single-core max. conductor cross-section	<b>6 mm<sup>2</sup></b>
--	-------------------------

Conductor Cross Section Awgkcmil Min	<b>24 AWG</b>
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	<b>10 AWG</b>
--------------------------------------	---------------

Multi-core min. conductor cross-section	<b>0.2 mm<sup>2</sup></b>
---	---------------------------

Multi-core max. conductor cross-section	<b>6 mm<sup>2</sup></b>
---	-------------------------

Multi-core min. conductor cross-section with ferrule	<b>0,25 mm<sup>2</sup></b>
--	----------------------------

Multi-core max. conductor cross-section with ferrule	<b>4 mm<sup>2</sup></b>
--	-------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	<b>0,5 mm<sup>2</sup></b>
--	---------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	<b>2.5 mm<sup>2</sup></b>
--	---------------------------

Min. Stripping Length	<b>8 mm</b>
-----------------------	-------------

Max. Stripping Length	<b>9 mm</b>
-----------------------	-------------

Internal cylindrical indicator	<b>A4</b>
--------------------------------	-----------

Tightening Torque Min	<b>0,5 Nm</b>
-----------------------	---------------

Tightening Torque Max	<b>0,8 Nm</b>
-----------------------	---------------

## DIMENSIONS

Width	<b>8 mm</b>
-------	-------------

Length	<b>69.60 mm</b>
--------	-----------------

Height Mr 35X75	<b>51 mm</b>
-----------------	--------------

Height MR 35x15	<b>58.50 mm</b>
-----------------	-----------------