


КЛЕММНЫЕ БЛОКИ > ВИНТОВЫЕ КЛЕММНЫЕ БЛОКИ > ПРОХОДНЫЕ КЛЕММЫ



АУК 10/16 4-полюсный Бежевый

Артикул (SKU): 395240

10-16 мм² винтовая проходная клемма — 4

Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 395240 |
| Единица Упаковки | 20 шт. |
| Номер таможенного тарифа | 853690950000 |
| Вес за единицу, включая упаковку | 0.1884 kg. |

Техническая информация

PRODUCT FEATURES

| | |
|---------------------------------------|----------------------|
| Number of Connections | 4 |
| Color | Beige |
| Number of Levels | 4 |
| Insulation Material | PA |
| UL 94 Flammability Class | V2 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-1 |
| Continuous Operating Temperature max. | 120 °C |
| Continuous Operating Temperature min. | -55 °C |

ELECTRICAL FEATURES

| | |
|-------------------------|--------------|
| Nominal Impulse Voltage | 8 Kv |
| Nominal Current | 76 A |
| Nominal Voltage | 750 V |
| Maximum Load Current | 76 A |

CONNECTION DATA

| | |
|--|---|
| Connection Type | Screw Connection |
| Single-core min. conductor cross-section | 2.5mm² / 0.5mm² mm² |
| Single-core max. conductor cross-section | 25mm² / 16mm² mm² |
| Conductor Cross Section Awgkcmil Min | 14 AWG / 20 AWG AWG |
| Conductor Cross Section Awgkcmil Max | 4 AWG / 6 AWG AWG |
| Multi-core min. conductor cross-section | 4mm² / 0.5mm² mm² |
| Multi-core max. conductor cross-section | 25mm² / 16mm² mm² |
| Multi-core min. conductor cross-section with ferrule | 2.5mm² / 0.5mm² mm² |
| Multi-core max. conductor cross-section with ferrule | 16mm² / 10mm² mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | 1.5mm² / 0.5mm² mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | 10mm² / 6mm² mm² |
| Min. Stripping Length | 14mm / 8mm mm |
| Max. Stripping Length | 16mm / 10mm mm |
| Internal cylindrical indicator | B6 |
| Tightening Torque Min | 1.2Nm / 1.2Nm Nm |
| Tightening Torque Max | 2.0Nm / 1.8Nm Nm |

DIMENSIONS

| | |
|-----------------|-----------------|
| Width | 11 mm |
| Length | 69,5 mm |
| Height Mr 35X75 | 653 mm |
| Height MR 35x15 | 72,80 mm |
| Height Mr 32 | 69,9 mm |