


КЛЕММНЫЕ БЛОКИ > ПРОЧИЕ ПРОДУКТЫ > РОЗЕТКА



FS 4 Серый

Артикул (SKU): 314009

Клемма быстрого подключения 4 мм²

Коммерческая информация

Код продажи продукта	314009
Единица Упаковки	80 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.0095 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	6
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	VO
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
Nominal Current	32 A
Nominal Voltage	800 V
Maximum Load Current	40 A

CONNECTION DATA

Connection Type	Faston baglanti
Single-core min. conductor cross-section	0,2 mm²
Single-core max. conductor cross-section	6 mm²
Conductor Cross Section Awgkcmil Min	24 AWG
Conductor Cross Section Awgkcmil Max	10 AWG
Multi-core min. conductor cross-section	0,2 mm²
Multi-core max. conductor cross-section	6 mm²
Multi-core min. conductor cross-section with ferrule	0,25 mm²
Multi-core max. conductor cross-section with ferrule	4 mm²

DIMENSIONS

Width	6,20 mm
Length	54,20 mm
Height Mr 35X75	51,50 mm
Height MR 35x15	59,00 mm
Height Mr 32	55,80 mm