



КЛЕММНЫЕ БЛОКИ &gt; ПРУЖИННЫЕ КЛЕММНЫЕ БЛОКИ &gt; ПРОХОДНЫЕ КЛЕММЫ

## PCY 2,5 Серый

Артикул (SKU): 364019

Клемма Cage Clamp 2,5 мм<sup>2</sup>, 1 вход-1 выход с гнездом

### Коммерческая информация

|                                  |                     |
|----------------------------------|---------------------|
| Код продажи продукта             | <b>364019</b>       |
| Единица Упаковки                 | <b>100 шт.</b>      |
| Номер таможенного тарифа         | <b>853690950000</b> |
| Вес за единицу, включая упаковку | <b>0.00509 kg.</b>  |

### Техническая информация

| PRODUCT FEATURES                      |                      |
|---------------------------------------|----------------------|
| Number of Connections                 | <b>2</b>             |
| Color                                 | <b>Grey</b>          |
| Number of Levels                      | <b>1</b>             |
| Insulation Material                   | <b>PA</b>            |
| UL 94 Flammability Class              | <b>V2</b>            |
| Impulse Voltage Category              | <b>3</b>             |
| Insulation Material Group             | <b>1</b>             |
| Pollution Degree                      | <b>3</b>             |
| Connection According to Standard      | <b>IEC 60947-7-1</b> |
| Continuous Operating Temperature max. | <b>120 °C</b>        |
| Continuous Operating Temperature min. | <b>-55 °C</b>        |

  

| ELECTRICAL FEATURES     |             |
|-------------------------|-------------|
| Nominal Impulse Voltage | <b>4 Kv</b> |
| Nominal Current         | <b>10 A</b> |

|                      |              |
|----------------------|--------------|
| Nominal Voltage      | <b>250 V</b> |
| Maximum Load Current | <b>10 A</b>  |

## CONNECTION DATA

|  |                            |
|--|----------------------------|
| Connection Type  | <b>Spring Connection</b>   |
| Single-core min. conductor cross-section   | <b>0,08 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section   | <b>4 mm<sup>2</sup></b>    |
| Conductor Cross Section Awgkcmil Min   | <b>28 AWG</b>              |
| Conductor Cross Section Awgkcmil Max   | <b>12 AWG</b>              |
| Multi-core min. conductor cross-section  | <b>0,08 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section  | <b>2,5 mm<sup>2</sup></b>  |
| Multi-core min. conductor cross-section with ferrule                               | <b>0,14 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section with ferrule                               | <b>2,5 mm<sup>2</sup></b>  |
| Min. Stripping Length  | <b>9 mm</b>                |
| Max. Stripping Length  | <b>10 mm</b>               |
| Internal cylindrical indicator   | <b>A3</b>                  |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve | <b>0,5 mm<sup>2</sup></b>  |

## DIMENSIONS

|                 |                 |
|-----------------|-----------------|
| Width           | <b>5,05 mm</b>  |
| Length          | <b>47,40 mm</b> |
| Height Mr 35X75 | <b>37,20 mm</b> |
| Height MR 35x15 | <b>44,70 mm</b> |